

DisplayPort to DVI Active Adapter Video Converter, DP ver 1.2, (M/F), 6-in. (15.24 cm), 50 pack

MODEL NUMBER: **P134-06NDVIV2BP**



Active adapter connects a DVI display to the DisplayPort (DP) output on your laptop or desktop computer for playing 1080p video.

Features

DisplayPort 1.2 to DVI Converters Connect DP Source to DVI Display This set includes 50 Tripp Lite P134-06N-DVI-V2 DisplayPort to DVI active adapters. Each adapter connects a DVI monitor, projector or television to the DisplayPort output on your PC, Mac, Chromebook, MacBook, Microsoft Surface or other compatible computer or tablet. They feature a male DP connector and a female DVI-I dual-link connector, allowing you to continue using your existing DVI display and DVI cable to transmit video signals without the expense of a new DP display.

Transmit Outstanding 1080p Video for High-Definition Presentations Ideal for classrooms, lecture halls and anywhere else you may need to connect to a DVI monitor, these DisplayPort to DVI converters support high-definition video resolutions up to 1920 x 1080 (1080p). The active adapters convert both Single-Mode and Dual-Mode (DP++) DisplayPort output. They come recommended for use with graphics cards, such as AMD Eyefinity, that do not output DP++ signals.

Ready to Use Right Out of the Package The plug-and-play DP to DVI adapters require no software, drivers or external power, work with both Windows and Mac operating systems, and are compatible with laptops, tablets and other devices equipped with a female DisplayPort. With its small size and built-in cable, the P134-06N-DVI-V2 is recommended for stowing in your laptop bag and carrying to school or the office.

Specifications

OVERVIEW	
UPC Code	037332237705
Technology	DVI; DisplayPort
VIDEO	

Highlights

- 50-piece bulk pack of P134-06N-DVI-V2 DisplayPort to DVI video adapters
- Delivers high-definition picture quality at resolutions up to 1920 x 1080 (1080p)
- Active adapter converts Single- and Dual-Mode DP++ output for viewing on VGA display
- Compact unit fits easily into briefcase or laptop bag for instant use anywhere
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect your newer laptop to an older DVI monitor in a lecture hall or conference room for a video presentation
- Add a secondary monitor to the PC or laptop in your office or home workspace
- Display menus, ads, promos, directions and other digital signage applications

System Requirements

- Source device with DisplayPort output
- Display device with DVI input

Package Includes

- (50) P134-06N-DVI-V2 DisplayPort 1.2 to DVI Active Converters (M/F), 6 in.



Powering Business Worldwide



Max Supported Video Resolution	1920 x 1080 @ 60Hz
INPUT	
Product Length (in.)	5.9
Product Length (ft.)	0.49
CONNECTIONS	
Side A - Connector 1	DISPLAYPORT (MALE)
Side B - Connector 1	DVI-I DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)
Connector Plating	Nickel
Contact Plating	Gold
PHYSICAL	
Color	Black
Material of Construction	ABS, PVC
Cable Jacket Material	PVC
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	4.5mm
Ferrite Core	No
Shipping Dimensions (hwd / in.)	4.10 x 15.75 x 17.75
Shipping Weight (kg)	2.09
Unit Dimensions (hwd / in.)	1.690 x 1.770 x 0.570
Unit Weight (lbs.)	0.22
Unit Weight (kg)	0.10
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
FEATURES & SPECIFICATIONS	
Displayport Specification	1.2
Driver Required	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	

Product Warranty Period (Worldwide)	3-year limited warranty
--	-------------------------

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.