



**Part Number :** [194360212](#)  
**Product Description :** MX150L 2 Circuit Rear Mount Flange Sealed Panel Mount Plug for 8 AWG Wire, without Gasket, Black  
**Series Number :** 19436  
**Status :** Active  
**Product Category :** Connector Housings



## Documents & Resources

**Drawings**  
[Drawing 194360212\\_sd.pdf](#)  
[Packaging Design Drawing PK-19436-001-001.pdf](#)

**3D Models and Design Files**  
[3D Model 194360212\\_stp.zip](#)

**Specifications**  
[Application Specification AS-19417-001-001.pdf](#)  
[Product Specification PS-19432-001-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Not Contained per D(2022)9120-DC (17 Jan 2023)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)  
- Eu RoHS  
- REACH SVHC  
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)  
- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Connector Housings
Series	19436
Description	MX150L 2 Circuit Rear Mount Flange Sealed Panel Mount Plug for 8 AWG Wire, without Gasket, Black
Application	Power, Wire-to-Wire
Comments	Mat Seal Color Red, Polarized to Mating Part; IP67 rated; Conforms to UL 1977; NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS)
Product Family	MX150L Industrial Sealed Connector System
Product Name	MX150L
UPC	800756904795

#### Physical

Circuits Detail	1x1
Circuits (maximum)	2
Color - Resin	Black
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	N/A
Lock to Mating Part	Yes
Number of Rows	1
Packaging Type	Bag
Panel Mount	Yes

Pitch - Mating Interface	7.62mm
Pitch - Termination Interface	7.62mm
Polarized to Mating Part	No
Ports	1
Stackable	No
Temperature Range - Operating	-40° to +125°C

---

**Mates With / Use With**

**Mates with Part(s)**

Description	Part Number
MX150L Receptacle Housings	<u>19432</u>