

A

B

C

D

E

F

G

A

B

C

D

E


F

G







MAPX

MODIFICATION

DATE



SECTION A-A'



RECOMMENDED PCB LAYOUT PCB图仅供参考

Note:

1.Material:

- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.20mm
- 1.3 Shell: copper alloy,t=0.25mm

2.Specification:

- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min
- 2.7 Temperature range: -30°C~80°C

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.30	X.	±5.°
.X	±0.25	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司

单位	MM
UNITS	
比例	1:1
SCALE	
日期	2021-04-16
DATE	

制图	尹先华
DRAWING	
审核	郭治富
CHKD	
核准	黄国荣
APPD	

制图料号	920-D52A2021S10109
PRODUCT PART NO.	
产品名称	MICRO 5S B型四脚全贴有边有柱外焊脚
PRODUCT NAME	长8.7LCP黑胶短端
角法	
VIEW	

版本	AD
VER	

版本	AD
VER	

版本	AD
VER	

版本	AD
VER	