



Part Number : [1200678311](#)
Product Description : Micro-Change (M12)
Single-Ended Cordset, 3 Poles, Female (90°) to
Pigtail with PNP LED Sensors, 0.34mm² PUR
LSOH Cable0.0m (32.81') Length
Series Number : 120067
Status : Active
Product Category : Circular Industrial
Cordsets
Engineering Number : 8030P1H09M100




Documents & Resources

Drawings
[Drawing 1200678311_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead; TBBA... per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120067
Description	Micro-Change (M12) Single-Ended Cordset, 3 Poles, Female (90°) to Pigtail with PNP LED Sensors, 0.34mm ² PUR LSOH Cable0.0m (32.81') Length
IP Rating	IP67
Product Family	Brad Micro-Change (M12) Connectors
Product Name	Micro-Change (M12)
Protocol	PROFIBUS
Region	Europe
Type	Single Ended
UPC	78172514713

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC/DC

Physical

Cable Diameter	4.32mm (.170")
Cable Length	10.0m (32.81')
Color - Cable Jacket	Black
Connector End A	Micro-Change (M12)
Connector End B	Pigtail
Coupling Style	Threaded
Gender	Female-Pigtail
Keyway	Single
LED Indicator	PNP Sensors
Material - Cable Jacket	PUR

Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Net Weight	266.377/g
Orientation	90° to Pigtail
Poles	3
Temperature Range - Operating	-30° to +90°C
Wire/Cable Type	UL 21198
Wire Size (AWG)	N/A