

USED IN ASSEMBLY	MATING CONFIG DETAIL	MATING NON-DELPHI PART NUMBER	MATING DELPHI PART NUMBER	PREVIOUS PART NUMBER
-	-	-	15448129	-

ASSOCIATED PARTS		
PART NUMBER	QTY	DESCRIPTION
15304841	2	LOCK SECONDARY TPA GT 20

SEE NOTE #1

CAVITY INFORMATION					
CAVITY NAME	TERMINAL	CABLE SEAL	CAVITY PLUG	*INSULATION CRIMP HEIGHT	*INSULATION CRIMP WIDTH
A1,A2,A7,A8,B1-B 12,C1-C12,D1,D2, D7,D8	15304701	-	-	3.15	2.8
A3-A6,D3-D6	15304722	-	-	3.65	4.2

NOTE

- SECONDARY TERMINAL LOCK 15304841 (TPA) SHOULD BE USED WITH WIRE O.D. < 3 MM
SECONDARY TERMINAL LOCK 15359121 (TPA) SHOULD BE USED WITH WIRE O.D. ≥ 3 MM

DELPHI	
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE WARREN, OH	
APVD1 JESUS PALOMO	DATE 26JA09
APVD2 JESUS PALOMO	26JA09
PUBLISHED DATE 12FE09	
DRAWING NAME ASM CONN 40 M GT 150 280	
DRAWING NUMBER 15416976	

APPLICATION DRAWING
UNLESS OTHERWISE SPECIFIED
WHEN APPLICABLE, EQUIVALENT PART NUMBERS MAY BE SUBSTITUTED FOR ANY OF THE PART NUMBERS SHOWN IN THE CHARTS ON THIS DRAWING.
* THE VALUES REPRESENT THE CAVITY CAPABILITIES. THE ACTUAL TERMINAL CRIMP DIMENSIONS MUST BE LESS THAN THE VALUES SHOWN.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Aptiv:](#)

[15416976](#)