




> PN Search


Millipacs™
HM2P08PDE2T0N9
> Communications Data
& Consumer division

FCI brings you more

✉ [Contact our sales/
technical support](#)✉ [Sample request](#)€ [Price request](#)📊 [Check distributor stock](#)[Home page](#)[Product quick search](#)

P/N Search

FCI Competitor

GORoHS/LF P/N
Search

Product type search

Alphabetical list

Connection type

Markets / Applications

[Product finder](#)[Literature](#)[Services](#)[Contact us](#)[Registered users](#)[Forgot password ?](#)[Register now](#)📄 [Download](#)> [Customer Drawing](#)> [Product Specification](#)> [3D Model](#)📐 [Mating half](#)

Not Available

🔧 [Alternative parts](#)

Not Available

🔧 [Application tooling](#)www.foehrenbach.be[Americas](#)[Asia Pacific](#)**Features Selected**

Product Type	Header
Contact Finish	Level 2 (0.8 microns Au)
Series	Module type B
Gender	Header
Orientation	Straight
#ofRows	5
# of Positions	125
Tail Lengths	Short Tails (3,7mm)
PCB Mounting	Press-fit
Shielded?	no

Other Properties

Housing Material	High Temperature Thermoplastic (UL94 V-0)
Contact Base Material	Phosphor Bronze
Operating Temperature	-55°C to +125°C
Signal Contact Current Rating	1.5 A @ 20°C, 1.0 A @ 70°C
Signal Contact Test Voltage (Fully Loaded)	750 Vrms
Signal Contact, Contact Resistance	20 milli ohms max
Signal Contact Insulation Resistance	10000 mega ohms min
Signal Contact Mating Force	0.75 N max per contact pair
Signal Contact Withdrawal Force	0.15 N min per contact pair
Signal Contact Hertz Stress	200 Kpsi min
Contact Levels	Refer to Customer Drawing
Signal Contact Normal Force	0.75 N min (EOL)
Approvals and Certification	UL and CSA Certified