

M8 Connector

TE Internal #: T4031017041-000

Wire-to-Panel, 4 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular

Connectors

View on TE.com >




Connectors > Circular Connectors > Standard Circular Connectors > M8 Panel Mount Solder Cups











Connector System: Wire-to-Panel

Connector Mounting Type: Panel Mount

Number of Positions: 4

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

All M8 Panel Mount Solder Cups (8)

Features

Product Type Features

| Product Type | Connector Assembly |
|-----------------------------------|----------------------|
| Accessory Color | Black |
| Assembly Requirement | Factory Assembled |
| Assembly Type | Electrical Connector |
| Circular Connector Shell Type | Metal-Shell |
| Connector Product Type | Connector Assembly |
| Connector System | Wire-to-Panel |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Receptacle |
| Shell Type | Metal |

Configuration Features

| Keying & Polarized Position Locations | A | |
|---------------------------------------|---|--|



| Factory Installed Backshell | No |
|---|-------------------|
| Keying | A |
| Number of Positions | 4 |
| Number of Power Positions | 0 |
| Number of Signal Positions | 4 |
| Contacts Preloaded | Yes |
| Electrical Characteristics | |
| Operating Voltage | 30 VAC |
| Body Features | |
| Peripheral Seal Material | Silicone |
| Environmental Protection | IP67 |
| O-Ring Material | Silicone |
| Environmental Protection Type | Sealed |
| Shell Plating Material | Nickel |
| Shell Base Material | Copper Alloy |
| Circular Connector Insulation Material Type | Polyamide 67 GF30 |
| Hermetically Sealed | Yes |
| Contact Features | |
| Contact Current Rating (Max) | 3 A |
| Reverse Gender | Yes |
| Circular Connector Contact Type | Socket |
| Mechanical Attachment | |
| Connector Mounting Type | Panel Mount |
| Polarization Code | A |
| Mating Alignment Type | Keyed |
| Housing Features | |
| Circular Connector Shell Size | 12.6 |
| Dimensions | |
| Wire Size | .25 – .75 mm² |
| Usage Conditions | |
| IP Dust Sealing Level | 6 |
| IP Water Sealing Level | IP67 |



| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
|-----------------------------|---------------------------|
| Operation/Application | |
| Circuit Application | Signal |
| Shielded | No |
| Industry Standards | |
| UL Flammability Rating | UL 94HB |
| Packaging Features | |
| Packaging Quantity | 1 |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | M8 Connector









Customers Also Bought













Documents

Product Drawings
M8.FMLE.PNLREAR.4POS.STR

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_T4031017041-000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4031017041-000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4031017041-000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Application Specification

English

Agency Approvals

UL

English