



- SPECIFICATIONS**
- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 50V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 100MΩ Min
 - 6、Withstanding Voltage: 500V AC/minute
 - 7、Material: PBT, UL94V-0

编 号	尺寸 (mm)	
	A	B
A1254-02Y	1.25	3.75
A1254-03Y	2.50	5.00
A1254-04Y	3.75	6.25
A1254-05Y	5.00	7.50
A1254-06Y	6.25	8.75
A1254-07Y	7.50	10.00
A1254-08Y	8.75	11.25
A1254-09Y	10.00	12.50
A1254-10Y	11.25	13.75
A1254-11Y	12.50	15.00
A1254-12Y	13.75	16.25
A1254-15Y	17.50	20.00



x ± 0.5	x ± 1
.x ± 0.30	.x ± 1
.xx ± 0.20	.xx ± 1
.xxx ± 0.005, xxx ± 1	

泰华电子有限公司
TaiHua Electronics Co., Ltd

单位 UNIT	MM	版本: NO	产品名称 Production name	GH孔座
比例 SCALE	1:1	页次: 1/1	产品料号 Product No	TH-A1254-NV
标准: APPROVED BY		日期: DATE	客户料号 Client No	
审核: CHECKED BY		制图: DRAWN BY		
		2022.3.2		