

BOARD-TO-BOARD HEADERS & RECEPTACLES



✓ Active

TE CONNECTIVITY (TE)

MINI BX RECPT ASSY 128P SEALED

AMP

2-530745-2

TE Internal Number: 2-530745-2 Mil-Spec: M55302/119-11

Not EU RoHS Compliant **EU ELV Compliant with Exemptions**

Connector Style Receptacle

Centerline (mm) 1.27

Centerline (Pitch) (in) .05

Number of Positions 128

Packaging Method Package



PRODUCT DRAWING

English



◆ 3D PDF

DOCUMENTATION

Product Drawings

RECEPTACLE ASSY, MINI BOX MILITARY, WITH LOW FORCE CONTACTS

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style Receptacle

Stabilizers Without

Row-to-Row Spacing 3.81 mm [.15 in]

PCB Mounting Orientation Vertical

Gasket Without

Connector Type Connector Assembly

Hybrid No

Boss Without

Strain Relief Without

Sealed Yes

Product Type Connector

Configuration Features

Number of Positions 128

Number of Rows 2

Stackable No

Body Features

Post Size .20 x .46 mm [.008 x .018 in]

Sealing Method Epoxy

Post Styles Posted

Color Gray

Contact Features

Contact Mating Area Plating Material Gold

Contact Mating Area Plating Thickness (µin) 50

Contact Layout Staggered

Contact Protection Without

Contact Base Material Beryllium Copper

Contact Type Socket

Solder Tail Contact Plating Material Tin-Lead over Nickel

Termination Features

Termination Post Length (mm) 3.56, 4.83

Termination Post Length (in) .19

Termination Method to PC Board Through Hole

Mechanical Attachment Mating Alignment Type Polarization **PCB Mount Retention** Without **Housing Features** Centerline (mm) 1.27 Centerline (Pitch) (in) .05 Housing Material LCP (Liquid Crystal Polymer) **Housing Color** Gray **Dimensions Height** 5.46 mm [.215 in] **Tail Length** 3.93 mm [.155 in] Operation/Application Pick and Place Cover Without For Use With Mates with Headers **Assembly Process Feature** None Industry Standards **Industry Standard Configuration** None **Packaging Features** Packaging Method Package Packaging Quantity 2 Other Comment Also see 1-530745-1 unsealed version.

Statement of Compliance

Statement of Compliance

PDF