

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 548 ...](#) » [SK 548](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - [Standard extruded heatsinks](#)
 - Extruded heatsinks for lock-in retaining spring
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components

▶ Cases f.case

▶ Connectors f.con

Standard extruded heatsinks

SK 548 ...

SK 548 50 SA

50 x 10 mm

Data sheet

add to request



Features

Technical Drawing

Service

thermal resistance R_{th}	10.45 - 4.65 K/W
surface	black anodised
height	10 mm
width B	50 mm
length	50 mm
plate thickness	2.5 mm