### **AMPMODU**


TE Internal #: 1375965-4

120 Position, 2 mm [.079 in] Centerline, PC/104 Connectors

View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > PC/104 Connectors



Number of Positions: 120

Centerline (Pitch): 2 mm [.079 in]

Number of Loaded Positions: 120

Contact Current Rating (Max): 3 A

## **Features**

### **Product Type Features**

Product Type Features	
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Standoffs	2
Stacking Configuration	Non-Stack Through
Number of Positions	120
Number of Loaded Positions	120
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	500 VAC
Insulation Resistance	1000 ΜΩ
Body Features	
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	3 A
Termination Features	

2.85 mm[.112 in]

Through Hole - Solder

Termination Post & Tail Length

Termination Method to PCB



PCB Mount Retention Type	None
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Nylon - GF
Centerline (Pitch)	2 mm[.079 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Assembly Process Feature	Board Standoff
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



# Customers Also Bought


















## **Documents**

## **Product Drawings**

PC104 PLUS NOSTKTHRU 2 STNDOFF

English

### **CAD Files**

Customer View Model ENG\_CVM\_1375965-4\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1375965-4\_D.3d\_stp.zip

English

**Customer View Model** 



ENG\_CVM\_1375965-4\_D.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPMODU\_INTERCONNECTION\_SYSTEM\_SECTION1AND2

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**UL Report** 

English