

POWER CABLE TUBING & ACCESSORIES









A Activ

TE CONNECTIVITY (TE)

MWTM-35/12-1200-S-(B25)

Raychem | MWTM

024335-002

TE Internal Number: 024335-002

Alias ID: 6-1190188-9, MWTM-35/12-1200-S-(B25)

EU RoHS Compliant
EU ELV Compliant

Product Availability AMERICAS

Technology Heat Shrink

Product Type Heat Shrink Tubing

Flammability Non-Flame-Retardant

Adhesive Coating Yes

DOCUMENTATION

Catalog Pages/Data Sheets

MWTM-MEDIUM-WALL-TUBING-CABLE-ACCESSORIES

PDF

English

TUBO DE PARED MEDIA (MWTM)

PDF

Spanish

Instruction Sheets

Instruction Sheet (non U.S.)

INSTALLATION INSTRUCTION FOR TUBING FOR POWER CABLES

PDF

English



Please review product documents or contact us for the latest agency approval information.

Product Type Features

Technology Heat Shrink
Product Type Heat Shrink Tubing
Adhesive Coating Yes
Shrink Ratio > 2.5:1
Wall Style (Excluding Adhesive) Single
Wall Thickness Medium
Material System Crosslinked Polyolefin
Coating Style Inline

Body Features

Flexibility Semi-Rigid
Color Black

Dimensions

Application Diameter (Max) (mm) 31.5
Application Diameter (Min) (mm) 13
Expanded Inside Diameter (Min) (mm) 35
Recovered Inside Diameter (Max) (mm) 12
Recovered Wall Thickness (Max) (mm) 2
Cut Length (mm) 1200

Usage Conditions

Flammability Non-Flame-Retardant

Operation/Application

Mechanical Resistance Against Mechanical Impact or Damage
Thermal Resistance Applicable for Low Temperatures, Applicable for High Temperatures, Flame-Retardant
Low Smoke Emission Yes
Non-Toxic & Non-Corrosive Emission Yes
Marine-Offshore-Shipbuilding Certified Yes
UV-Stabilized Yes
Free of Lead, Cadmium, Heavy Metals Yes
Emission Free No

Industry Standards

Standards IEC 60684-3-214, IEC 60684-3-246, IEC 60684-3-247, HD631.2 **UL Rating** No **CSA Certified** No

Product Availability

Product Availability AMERICAS

Other

| C | Other Colors Available No |
|---|---------------------------|
| | Statement of Compliance |

Statement of Compliance

PDF