

1		2		3		4		5		6		7		8					
SAMZO		REAC/ROHS												REV	ECN NO	DESCRIPTION	DESIGN	APPROVAL	DATE
														A1	NEW	Replace frame			2018.06.12

技术要求:

Technical requirements:

1. 打铜底0.5-1UM, 镍底2-2.5UM, 哑锡(镍)3-5UM。

Copper base 0.5 - 1 UM, nickel base 2 - 2.5 UM, matte tin 3 - 5 UM.

2. 不得有脚变形, 毛刺等缺陷。

There shall be no defects such as pin deformation and burrs.

3. 插脚尖部符合可焊性要求。

The tip of the insertion pin shall meet the solderability requirements.

4. 螺纹需符合通止规要求。

The thread shall meet the requirements of the go and no-go gauge.

5. 材质: 黄铜H65。

Material: Brass H65.

6. 过载电流: 120A

Overload current: 120A

7. 螺孔为拉伸M5

The screw holes are press-riveted M5

8. 未标注尺寸公差值按GB/T1184-1996H级

Unmarked dimensional tolerance values are in accordance with Grade H of GB/T1184-1996

10400 80 S * M5

SERISE: 10*40mm

HIGH: H8.0mm

WELDING: S:SMT

CUSTOM CODE: ROUTINE

0-Tin plating

1-Nickel-plated

SCREW HOLE: M5

11

8

40

2.8

1.2

拉伸M5

40

10

7.2

2.5

2.8

拉伸M5

37.5

7.2

2.8

3

拉伸M5

PCB LAYOUT

ITEM	DESCRIPTION	MATERIAL	QTY	FINISH/COLOR							FIRST VIEW		The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM	TITLE::		
A	Subject	H62(Y2)	1	tin plating										10*40*8mm (M5)		
											GENERAL TOLERANCE			DWG NO: 10400S-P09103		
											SCALE	1:1		UNIT	mm	PART NO: 10400S-2302103
					DESIGN	WANGGUIFA	2018.06.12									MODEL NO: 1040080S-*-M5
					CHECKED	ZHENGUILAN	2018.06.12				SAMZO COMPONENTS					NAME:
F					APPROVED	LILIANJIANG	2018.06.14				Electronic switch and connector manufacturer					PCB soldering terminal
	1	2	3	4	5	6	7	8								