# 3-2331102-1 ACTIVE

### **LEAVYSEAL**

TE Internal #: 3-2331102-1

PCB Mount Header, Vertical, Wire-to-Board, 46 Position, 4 mm [. 157 in] Centerline, Fully Shrouded, Silver (Ag), Through Hole -

Solder, LEAVYSEAL

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 46

Centerline (Pitch): 4 mm [ .157 in ]

Sealable: Yes

PCB Mount Orientation: Vertical

### **Features**

### **Product Type Features**

1 Toduct Type Leatures	
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	46
PCB Mount Orientation	Vertical
Number of Rows	3
Body Features	
Primary Product Color	Blue

C

Connector & Keying Code



Contact Size	1.5mm
Contact Type	Tab
Mating Tab Width	1.5 mm[.059 in]
Mating Tab Thickness	.64 mm[.025 in]
Contact Mating Area Plating Material	Silver (Ag)
Contact Current Rating (Max)	23 A
Termination Features	
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	4 mm[.157 in]
Usage Conditions	
Operating Temperature (Max)	130 °C[266 °F]
Operating Temperature Range	-40 - 130 °C[-40 - 266 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Quantity	90
Packaging Method	Box

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2022 (224)



$\square$	n 0 +	aantain	REACH	CV/IIC
DOES	$\Gamma(C)$	contain	KFAU.H	$\Sigma V \square U$

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

### Solder Process Capability

Not reviewed for solder process capability

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**




## Also in the Series | LEAVYSEAL













# Customers Also Bought


















## **Documents**

**Product Drawings** 

TAB HEADER 46POS.

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-2331102-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2331102-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2331102-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

PCB Mount Header, Vertical, Wire-to-Board, 46 Position, 4 mm [.157 in] Centerline, Fully Shrouded, Silver (Ag), Through Hole - Solder, LEAVYSEAL



Product Specifications
Application Specification

English