

You are here: [Products](#) » [Connectors f.con](#) » [PCB connectors](#) » [Male headers](#) » [SL 2 ... / SL 22 ...](#) » [SL 22 190](#)



- Heatsinks f.cool
- Cases f.case
- ▼ Connectors f.con
 - Sockets
 - ▼ PCB connectors
 - Male headers
 - Female headers
 - Direct female connectors
 - Jumpers
 - IDC-connectors
 - D-Sub connectors
 - Brackets for PC
 - Optoelectronics

Male headers

SL 2 ... / SL 22 ...

SL 22 190 10 Z
two rows, $\square$ 0.635 mm

add to request



FeaturesTechnical DrawingVariantsServiceAccessories / related products

Article 1-10 of 17

1 | 2 > >>

Number per page: 10

Picture	Name
	►Female headers / BL 2 ... Stamped contact spring (fork contact), for $\square$ 0...
	►Female headers / BL 4 ... Stamped contact spring (fork contact), for $\square$ 0...
	►Female headers / BL LP 2 ... for $\square$ 0.635 mm
	►Female headers / BL LP 4 ... for square 0.635 mm, packing in a bar magazine (min. 4 contacts)
	►Female headers / BL 12 ... for $\square$ 0.635 mm, can be put through from above and below
	►Female headers / BL 21 ... $\square$ 0.635 mm, can be put through from above
	►Female headers / BL 6 ... for $\square$ 0.635 mm and up to 0.85 mm Ø
	►Female headers / BL 8 ... for $\square$ 0.635 mm and up to 0.85 mm Ø, packing (option) bar magazine
	►Female headers / MK 221 ... $\square$ 0.635 mm and up to 0.85 mm Ø; No capillary action when soldering due to protected contact insert...
	►Female headers / BL 10 ... $\square$ 0.635 mm and up to 0.85 mm Ø, with aligned contact pin

Article 1-10 of 17

1 | 2 > >>