Interconnect Solutions



DCM13W6SF225

Part Number Details

series	COMBO D
category	D Sub
line	D Sub
brand	Cannon
ittPartNo	DCM-13W6S-F225

General	Combo D Series: D-Subminiature offering mixed layouts	
Wire Gauge Range AWG	AWG 8-26	
Mating Cycles	50	
Contact Arrangement	13W6 (7 contacts size 20, 6 empty size 8 cavities)	
Dielectric Withstanding Voltage	500 VAC at sea level	
Current Rating Signal Contacts	7.5 max	
Contact Resistance	10 milli Ohm max	
Operating Temperature	-55°/+125°	
Salt Spray Test	20 hours	
Shell Material	Passivated stainless steel	
Shell Finish	Stainless steel shell	
Insulator Material	Thermoplastic, type PCT UL 94V-0	
Insulator Color	black	
Gender	Socket	

Contact Type		Solder pot	
Contact Material		copper alloy	
Contact Finish		gold flash (Performance Class 3)	
Mounting Method		.120" (3,05mm) Through Hole	
rohsCompliantString	material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2011/65/EU		
rohsCompliantFlag	YES		

Drawings for this part are available. Upon request your will be asked to provide your contact information at which time the appropriate drawing files will be sent to you via email.

Request 3D Model

A datasheet is available for download.

Download Datasheet PDF

Check the stock availability of this product at our distributors.

Check Stock Now

Part Number	Distributor	Qty	Location
DCM13W6SF225	Arrow Electronics	96	United States
DCM13W6SF225	PEI-Genesis, Inc.	101	United States

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Contact Us" at the top of every page.

line: D Sub: ittPartNo: DCM-13W6S-F225

Request a Quote