





SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1000V AC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.54	8.26	2x14P	33.02	36.96
2x3P	5.08	9.02	2x15P	35.56	39.50
2x4P	7.62	11.56	2x16P	38.10	42.04
2x5P	10.16	14.10	2x17P	40.64	44.58
2x6P	12.70	16.64	2x18P	43.18	47.12
2x7P	15.24	19.18	2x19P	45.72	49.66
2x8P	17.78	21.72	2x20P	48.26	52.20
2x9P	20.32	24.26	2x21P	50.80	54.74
2x10P	22.86	26.80	2x22P	53.34	57.28
2x11P	25.40	29.34	2x23P	55.88	59.82
2x12P	27.94	31.88	2x24P	58.42	62.36
2x13P	30.48	34.42	2x25P	60.96	64.90



CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE 2.54mm PITCH Dual Row HOUSING		
mm	3:1	1 of 1			
DRWN	CHK'D	APPR			
Wenmin Luo	Diankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION		DRAWING NO. A2549HI-2xXP	
x.xx±0.25					
x.xx±0.20					
x.xxx±0.15					
ANGLES ±1°				REV A1	