




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1624 – 4107 CMA**

Mating Tab Width: **6.35 mm [.25 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	19.18 mm[.755 in]
Compatible Insulation Diameter Range	3.1 – 4.3 mm[.12 – .17 in]
Wire Size	1624 – 4107 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 58524-1 PROCRIMPER TOOL & DIE	TE Part # 154509-2 250 FASTON HSG.,REC.,1 POS, NATRUAL	TE Part # 1-521785-1 250 FASTON HSG.,REC.,2 POS, NATRUAL	TE Part # 314917-1 EXT TL 250 U-POD STR IS9726
TE Part # 5-154509-4 250 FASTON HSG. REC 1P BLACK	TE Part # 154509-4 250 FASTON HSG.,REC.,1 POS, NATRUAL	TE Part # 58524-2 PROCRIMPER DIE	TE Part # 2150016-1 OCEAN_2.0_Applicator-E-100F180F- REM
TE Part # 2150016-2 OCEAN_2.0_Applicator-E-100F180F- REA	TE Part # 2423313-1 HOUSING, RECEPTACLE, FASTON, 250 SERIES	TE Part # 2423314-1 HOUSING, RECEPTACLE, FASTON, 250 SERIES	TE Part # 346697-3 250 FASTON,REC.,20-16 AWG,PB
KIT TE Part # 7-2150016-7 OCEAN_2.0_SPARE_PART_KIT- 100F180F			

Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(132)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(134)



Quick Disconnects(426)



Splices(4)

Customers Also Bought




TE Part #521368-2
ULTRA-POD 250 ASSY REC 22-18 AWG TPBR




TE Part #521367-1
ULTRA POD: Straight, Receptacle Assembly, Unplated, .250 inch



TE Part #62813-1
250 FASTON FLAG REC 22-18 AWG BR




TE Part #61399-1
312 FASTON REC 16-12 AWG TPBR



TE Part #63306-2
250 FASTON REC 18-14 AWG TPBR




TE Part #521411-1
ULTRA-POD 250 ASY REC 22-18 AWG BR



TE Part #63538-1
250 FASTON FLAG REC 18-14 BR



TE Part #42800-1
187 FASTON REC 20-16 AWG BR



TE Part #63435-1
250 FASTON REC 14-10 AWG SPBR

Documents



Product Drawings

250 FASTON REC 18-14 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63306-1_BC.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63306-1_BC.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63306-1_BC.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English

UL Report

English