



Features

- Low Forward voltage drop
- Fast switching



SOT-363



Equivalent Circuit

Absolute Maximum Ratings(T_A=25℃)

Symbol	Parameter	Value	Unit
V _{RM}	Non-Repetitive Peak reverse voltage	40	V
V _R	DC Blocking Voltage		
I _O	Average Rectified Output Current	200	mA
P _d	Power Dissipation	200	mW
R _{θJA}	Thermal Resistance From Junction To Ambient	625	℃/W
T _J	Operating Junction Temperature Range	-125	℃
T _{stg}	Storage Temperature Range	-65~125	℃

Electrical Characteristics (T_A=25℃ unless otherwise specified)





Symbol	Parameter	Test conditions	Min	Max	Unit
V _(BR)	Reverse breakdown voltage	I _R =10μA	40		V
I _R	Reverse current	V _R =30V		200	nA
V _F	Forward voltage	I _F =1mA		380	mV
		I _F =40mA		1000	
C _D	Diode capacitance	V _R =0V, f=1MHz		5	pF
t _{rr}	Reverse recovery time	I _F =10mA, I _R =I _F =1mA, R _L =100Ω		5	nS

Ordering information


Product ID	Marking	Naming rule	Pack	Qty(PCS)
BAS40DW-04	K44	BAS40DW-04 产品名称 product name	SOT-363	3000



Typical Characteristics



SOT-363 Package Outline Dimensions



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.150	0.004	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°