

Crimp Information Sheet

DELPHI

Terminal Part Number: 13580635
Surface Plating: F.SN3
Material Thickness [mm]: 0,25
Cross Section [mm²]: 0,35 | 0,50 | 0,75

*This document is non-contractual
and for information only.*

*For more information, please
consult your local sales office*

Cable Type codes: 2010
Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY
Insulation Range Φ [mm]: 1,20 - 1,90
Seal(s): NONE

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2010 0,35		1,34	50	0,95	0,05	1,65	0,10	1,60	0,10	1,90	0,10
2010 0,50		1,50	80	1,05	0,05	1,65	0,10	1,80	0,10	2,00	0,10
2010 0,75		1,75	120	1,15	0,05	1,65	0,10	2,00	0,10	2,05	0,10

Cable type code legend:

2010: ACW0219, FIAT T2 FLRY, FL RENAULT R1, FL RENAULT R3, FLR
(AGP0219), FLR2X-A, FLR4Y-A, FLR9Y, FLRX-B, FLRY-A, FLRYB, FLRY-B



Industry Designator: DIN

Conductor Material: COPPER

Conductor Plating: NONE

Insul. Material: PA, POLYOLEFIN, PP, PVC, SYNTHRESIN, XLCOPOLY, XLPBT, XLPE,
XLPE/PVDF, XLPVC

Insul. Wall Designator: THIN



Crimp Information Sheet

DELPHI

Terminal Part Number: 13580635

Surface Plating: F.SN3

Material Thickness [mm]: 0,25

Cross Section [mm²]: 0,35

*This document is non-contractual
and for information only.*

*For more information, please
consult your local sales office*

Cable Type codes: 2010 + 2010

Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY

Seal(s): NONE

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2010 0,35 + 2010 0,35		1,34 + 1,34	93	1,10	0,05	1,75	0,10	2,05	0,10	2,05	0,10

Cable type code legend:

2010: ACW0219, FIAT T2 FLRY, FL RENAULT R1, FL RENAULT R3, FLR (AGP0219), FLR2X-A, FLR4Y-A, FLR9Y, FLRX-B, FLRY-A, FLRYB, FLRY-B



Industry Designator: DIN

Conductor Material: COPPER

Conductor Plating: NONE

Insul. Material: PA, POLYOLEFIN, PP, PVC, SYNTHRESIN, XLCOPOLY, XLPBT, XLPE, XLPE/PVDF, XLPVC

Insul. Wall Designator: THIN



Terminal Part Number: 13580635
Surface Plating: F.SN3
Material Thickness [mm]: 0,25
Cross Section [mm²]: 0,50

*This document is non-contractual
and for information only.*



*For more information, please
consult your local sales office*

Cable Type codes: 2016
Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY
Insulation Range Φ[mm]: 0,75 - 1,00
Seal(s): NONE

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2016 0,50		0,88	75	1,05	0,05	1,65	0,10	1,90	0,10	2,00	0,10

Cable type code legend:

2016: DIN-CORE
Industry Designator: DIN
Conductor Material: COPPER
Conductor Plating: SN
Insul. Material: NONE
Insul. Wall Designator: NONE



Terminal Part Number: 13580635
Surface Plating: F.SN3
Material Thickness [mm]: 0,25
Cross Section [mm²]: 0,60

*This document is non-contractual
and for information only.*

*For more information, please
consult your local sales office*

Cable Type codes: 2069
Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY
Insulation Range Φ[mm]: 0,00 - 0,00
Seal(s): NONE

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2069 0,60		0,00	75	1,10	0,05	1,65	0,10	1,90	0,10	2,00	0,10

Cable type code legend:

2069: BRAIDED SHIELD
Industry Designator: DIN/IS
Conductor Material: COPPER
Conductor Plating: NONE
Insul. Material: NONE
Insul. Wall Designator: NONE

