

# FB-PS-MB-Y/EX - Power supply unit



2316148

<https://www.phoenixcontact.com/us/products/2316148>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Four-channel redundant fieldbus power supply base. Host connections are for two Yokogawa AKB336 20-pin cables.



## Product description

Yokogawa four-channel, redundant fieldbus power supply base with host connectors for two AKB336 Yokogawa 20-pin cables.

## Your advantages

- Built-in relay diagnostics
- Redundancy

## Commercial data

Item number	2316148
Packing unit	1 pc
Sales key	DN11
Product key	DNC1Z1
Catalog page	Page 459 (C-6-2019)
GTIN	4055626128368
Weight per piece (including packing)	1,136.8 g
Weight per piece (excluding packing)	1,136.8 g
Customs tariff number	85366990
Country of origin	US

# FB-PS-MB-Y/EX - Power supply unit



2316148

<https://www.phoenixcontact.com/us/products/2316148>

## Technical data

### Notes

#### Utilization restriction

##### CCCex note

Use in potentially explosive areas is not permitted in China.

### Product properties

#### Product type

Device coupler

### Output data

#### Signal

##### Output name

Alarm

### Connection data

#### Supply

##### Conductor cross section, flexible

0.20 mm<sup>2</sup> ... 2.50 mm<sup>2</sup>

##### Conductor cross section, rigid

0.20 mm<sup>2</sup> ... 2.50 mm<sup>2</sup>

##### Conductor cross section AWG

30 ... 12

### Ex data

#### Safety data

##### Inductance Li

17.8 mH (trunk and host)

##### Max. output voltage U<sub>o</sub>

30 V DC (trunk and host)

### Interfaces

#### Data: Yokogawa DCS cabling system

##### Number of connections

2

##### Connection method

AKB336 cable

##### Tightening torque

0.4 Nm ... 0.5 Nm (AKB336 cable)

### Dimensions

#### Width

180 mm

#### Height

77 mm

#### Depth

180 mm

### Environmental and real-life conditions

#### Ambient conditions

##### Degree of protection

IP20

##### Ambient temperature (operation)

-40 °C ... 70 °C

##### Ambient temperature (storage/transport)

-40 °C ... 85 °C

##### Max. permissible relative humidity (operation)

95 % (non-condensing)

# FB-PS-MB-Y/EX - Power supply unit



2316148

<https://www.phoenixcontact.com/us/products/2316148>

Permissible humidity (operation)	95 % (non-condensing)
----------------------------------	-----------------------

## Approvals

### ATEX

Identification	II 3 G Ex ec nC IIC T4 Gc
Certificate	Sira 11ATEX4216X

### IECEX

Identification	Ex ec nC IIC T4 Gc
Certificate	IECEX SIR 11.0097X

### UKCA Ex (UKEX)

Identification	II 3G Ex ec nC IIC T4 Gc
Certificate	PxCAI22UKEx2316132X

### Ex data

CSA, USA/Canada	Class I, Div. 2, Groups A, B, C, D; Ex nA nC IIC T4 Class I, Zone 2, AEx nA nC IIC T4
-----------------	--

## Standards and regulations

### Standards

Standards/regulations	NE21
	EN 61326

### Standards/regulations

Standards/regulations	Ring wave noise immunity in acc. with IEC 61000-4-12
-----------------------	--

### Standards/regulations

Standards/regulations	Dry heat in acc. with IEC 61131-2
-----------------------	-----------------------------------

### Standards/regulations

Standards/regulations	Damp heat in acc. with IEC 61131-2
-----------------------	------------------------------------

### Standards/regulations

Standards/regulations	Shock and vibration in acc. with EN 61131-2 and EN 50178
Standards/regulations	IEC 61158-2

# FB-PS-MB-Y/EX - Power supply unit



2316148

<https://www.phoenixcontact.com/us/products/2316148>

## Classifications

### ECLASS

ECLASS-11.0	27242692
ECLASS-12.0	27242692
ECLASS-13.0	27242692

### ETIM

ETIM 9.0	EC002584
----------	----------

### UNSPSC

UNSPSC 21.0	32151600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

# FB-PS-MB-Y/EX - Power supply unit

2316148

<https://www.phoenixcontact.com/us/products/2316148>



## Accessories

### FB-PS-PLUG-24DC/28DC/0.5/EX - Power module

2316132

<https://www.phoenixcontact.com/us/products/2316132>



Power supply plug for fieldbus system in hazardous locations. Provides 500 mA @ 28 V DC to couplers along the trunk.

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)