

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON sleeve housing B16, for double locking latch, height 76 mm, with M20 thread, straight cable outlet, EMC version

## Commercial data

Item number	1587360
Packing unit	5 pc
Minimum order quantity	1 pc
Product key	BF7AAD
Catalog page	Page 587 (PC-2011)
GTIN	4046356479240
Weight per piece (including packing)	220.38 g
Weight per piece (excluding packing)	220.38 g
Country of origin	CZ

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

## Technical data


### Notes

General	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
---------	---------------------------------------------------------------

### Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	EMC
Type	B16
No. of cable outlets	1
Type of the screw connection	1x M20
Shielded	yes
Cable outlet	straight
Pg screw connection	none

### Dimensions

Dimensional drawing	
Width	43 mm
Height	76 mm
Length	94 mm

### Material specifications

Housing material	die-cast aluminum
Housing surface material	EMC coating, silver

### Mechanical properties

#### Mechanical data

Type of the screw connection	1x M20
Locking type	Pin


### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 100 °C


## Drawings

Dimensional drawing



Dimensional drawing

Diagram



Shield attenuation

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

## Classifications

### ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

## Accessories

### G-INS-M20-S68N-PNES-GY - Cable gland

1411125

<https://www.phoenixcontact.com/us/products/1411125>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver-grey RAL 7001

---

### G-INS-M20-S68N-PNES-BK - Cable gland

1411133

<https://www.phoenixcontact.com/us/products/1411133>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: jet black RAL 9005

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing

1587360

<https://www.phoenixcontact.com/us/products/1587360>



## G-INS-M20-S68N-NNES-S - Cable gland

1411163

<https://www.phoenixcontact.com/us/products/1411163>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

---

## HC-M-KV-M20(11-16) - Cable gland

1645998

<https://www.phoenixcontact.com/us/products/1645998>



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

## G-INSEC-M20-S68N-NCRS-S - Cable gland

1411189

<https://www.phoenixcontact.com/us/products/1411189>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 9 mm ... 13 mm, shielding: yes, connecting thread: M20 x 1.5, color: silver, with O-ring

---

## G-INESR-M20-S68N-NEPDS-S - Cable gland

1415192

<https://www.phoenixcontact.com/us/products/1415192>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm ... 13 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with external strain relief, with O-ring

## HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing

1587360

<https://www.phoenixcontact.com/us/products/1587360>



## HC-M-KV-T-M20 - Cable gland

1646188

<https://www.phoenixcontact.com/us/products/1646188>

Metal screw connection with cable bend protection and strain relief, thread length: 6 mm, cable sealing area: 7.5 - 15 mm, clamping area: 10 - 16 mm, SW 24, screw connection: M20



---

## REDUC-M-KV-M20/M16 - Reducing adapter

1647611

<https://www.phoenixcontact.com/us/products/1647611>

Reducing adapter, connecting thread: M20 x 1.5, color: silver, with O-ring





# HC-B 16-TFQ-76/O1STM20G-EMV - EMC housing



1587360

<https://www.phoenixcontact.com/us/products/1587360>

## ENLAR-M-KV-M20/M25 - Extension adapter

1647666

<https://www.phoenixcontact.com/us/products/1647666>

Extension adapter, connecting thread: M20 x 1.5, color: silver, with O-ring



---

## HC-M-BS-M20 - Screw plug

1645846

<https://www.phoenixcontact.com/us/products/1645846>

Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M20 x 1.5, color: silver



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)