



Connectors > Power Connectors > Circular Power > Circular Power Connectors > Circular Connector, CMC Series 3



Connector Product Type: **Housing**
Operating Voltage: **600 VDC**
Wire Size: **10 – 16 AWG**
Connector System: **Wire-to-Panel**
Number of Positions: **7**

[All Circular Connector, CMC Series 3 \(10\)](#)

Features

Product Type Features

Connector Product Type	Housing
Connector System	Wire-to-Panel
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	Metal-Shell

Configuration Features

Reverse Numbering	Without
Number of Positions	7
Number of Power Positions	7
Number of Signal Positions	0

Electrical Characteristics

--	--



Operating Voltage	600 VAC
-------------------	---------

Contact Features

Reverse Gender	Yes
Contact Type	Socket
Contact Current Rating (Max)	25 A
Contact Protection	With

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Alignment	With
Panel Mount Feature Type	Flange with Mounting Holes
Mating Retention Type	Threaded Coupling
Thread Size	1-3/8 - 18 UNEF-2A
Connector Mounting Type	Panel Mount
Mating Retention	With
Panel Mount Feature	With

Housing Features

Body Orientation	Straight
Housing Color	Black
Housing Material	Thermoplastic
Circular Connector Shell Size	28

Dimensions

Compatible Insulation Diameter Range	5.59 mm[.22 in]
Wire Size	10 – 16 AWG

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Fluid Resistance	None

Operation/Application

Circuit Application	Power & Signal
Shielded	No

Industry Standards



UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	10
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-AM71-C83998R
Circular Connector, CMC Series 3



TE Part # 211904-1
CMC DUST CAP ASSM SIZE 28



Also in the Series | AMP CPC



Circular Power Connectors(458)



Connector Backshells(1)



Connector Caps & Covers(19)



Connector Contacts(6)



Connector Hardware(12)




Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)




Insertion & Extraction Tools(1)




Sealing Sleeves(2)

Customers Also Bought



TE Part #213843-4
PWRBAND SKT CNT ASSY,8-10,L.P.



TE Part #208945-8
SZ 28 UNASSM KIT,CMC



TE Part #208721-1
RECEPT ASSY,SZ 14,CMC



TE Part #1776088-1
Circular Plastic Connector, CMC Series 4



TE Part #66741-6
TYPE XII FEMALE CONT (L.P.)



TE Part #41580
RING TERMINAL 24-20 AWG TPBR



TE Part #60372-1
SPLICE 1200-2600 .020 BR



TE Part #3-770060-1
MINI AMP-IN PTLP/PHBZ



Documents

Product Drawings

CMC RECPT ASSEMBLY SIZE 28

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_208485-1_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_208485-1_K.3d_igs.zip

English

Customer View Model

ENG_CVM_208485-1_K.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_208485-1_W.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_208485-1_W.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_208485-1_W.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1-1773902-9_CPC_Catalog

English

1-1773902-9_CPC_Catalog

1-1773902-9_CPC_Catalog

German

1-1773902-9_CPC_Catalog

Japanese

AMP Circular Connectors for Commercial Signal & Power Applications Continued

English

Product Specifications

Product Specification

English



Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English