




+ CONNECTORS

CONNECTOR HOUSINGS



✓ Active

TE CONNECTIVITY (TE)

# 64P.FEMALE CONN ASSY FOR MM EC

AMP | MQS

3-284272-0

TE Internal Number: 3-284272-0

EU RoHS Compliant

EU ELV Compliant

Connector System Wire-to-Board, Wire-to-Device, Wire-to-Wire

Connector Style Housing for female terminals

Mating Tab Width .64 mm [ .025 in ]

Sealable Yes

Centerline (Pitch) (in) .098

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

## DOCUMENTATION

Product Drawings

### 64 POSITIONS FEMALE CONNECTOR

PDF

English

CAD Files

### Customer View Model

2D\_DXF.ZIP

English

### 3D PDF

PDF

3D

Customer View Model

3D\_IGS.ZIP

English

Customer View Model

3D\_STP.ZIP

English

Product Specifications

Product Specification

64+64 POS. MQS HEADER AND REC. CONN. PRODUCT SPECIFICATION

PDF

English

64+64 POS. MQS HEADER AND REC. CONN. PRODUCT SPECIFICATION

TIF

English

Instruction Sheets

Instruction Sheet (non U.S.)

64 Pos. Female Conns. For Engine Management

TIF

English

64 Pos. Female Conns. For Engine Management

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

**Connector System** Wire-to-Board, Wire-to-Device, Wire-to-Wire

**Connector Style** Housing for female terminals

**Sealable** Yes

**Hybrid Connector** No

**Terminates To** Wire & Cable

**Primary Locking Feature** Integrated in Housing

**Strain Relief** No

**Row-to-Row Spacing** 2.54 mm [ .1 in ]

Configuration Features

**Number of Positions** 64

**Number of Rows** 4

Electrical Characteristics

Nominal Voltage Architecture (V) 12, 24  
Operating Voltage (VDC) 24

Body Features

Color Black  
Cable Exit Angle 90°  
Body Material PA GF

Contact Features

Mating Tab Width .64 mm [ .025 in ]

Mechanical Attachment

Mounting Feature No  
Terminal Position Assurance Yes  
Polarized No

Housing Features

Centerline (Pitch) (in) .098  
Pitch (mm) 2.5

Dimensions

Width 38.5 mm [ 1.516 in ]  
Height 68 mm [ 2.677 in ]  
Length 88.8 mm [ 3.496 in ]

Usage Conditions

Operating Temperature Range -40 – 125 °C [ -40 – 257 °F ]  
Operating Temperature (Max) (°C) 70, 75, 80, 85, 90, 100, 105, 110, 120, 125  
Operating Temperature (Max) (°F) 158, 167, 176, 185, 194, 212, 221, 230, 248, 257

Operation/Application

Circuit Application Signal

Industry Standards

Degree of Protection Other

Packaging Features

Packaging Method Box  
Packaging Quantity 155

Other

Connector Position Assurance Capable No  
Serviceable Yes

Statement of Compliance

