



Power Double Lock

TE Internal #: 179841-1
Header, Receptacle, Wire-to-Board, 6 Position, 3.96 mm [.156 in]
Centerline, Printed Circuit Board, Power Double Lock, Rectangular
Power Connectors

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > STD Temp Power Double Lock Header



Rectangular Power Connector Type: **Header**
Connector & Housing Type: **Receptacle**
Connector System: **Wire-to-Board**
Number of Positions: **6**
Centerline (Pitch): **3.96 mm [.156 in]**

[All STD Temp Power Double Lock Header \(22\)](#)

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	6
PCB Mount Orientation	Vertical
Number of Power Positions	6
Number of Rows	2

Electrical Characteristics

--	--



Operating Voltage	50 VAC
-------------------	--------

Contact Features

PCB Contact Termination Area Plating Material Thickness	1 μm[39.37 μin]
Contact Layout	Matrix
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	8 A, 14 A
Contact Retention Within Housing	Without
Contact Type	Tab
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	1 μm[39.37 μin]

Termination Features

Termination Post & Tail Length	3.8 mm[.148 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Post
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Nylon 6/6 GF

Dimensions

Compatible Insulation Diameter (Max)	3.1 mm[.122 in]
Connector Height	14.6 mm
PCB Thickness (Recommended)	.06 mm[1.6 in]
Product Width	13.6 mm
Product Length	14.8 mm



Wire Size	.128 – 1.308 mm ²
Row-to-Row Spacing	4.6 mm[.181 in]

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame) According IEC 60335-1 Edition 06/2001

Packaging Features

Packaging Quantity	272
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 177901-1
POWER DBL LOCK PLUG HSG 6P

TE Part # 179839-9
AMP POWER D/LOCK T/HDR ASSY 3P

Also in the Series | Power Double Lock

Connector Contacts(24)

Connector Hardware(14)

Insertion & Extraction Tools(2)

Rectangular Power Connectors(283)

Customers Also Bought

TE Part #9-6437287-9
SUPERSEAL Connector Headers: 1.0 mm

TE Part #1376383-1
5mm B-T-W Conn. 3P HDR ASSEMBL

TE Part #1-1969688-4
PTL 1X4 PCB HEADER VERT HITEMP KEY A LGR

TE Part #63982-1
187 FASTON TAB TPBR

TE Part #1376384-1
5mm B-T-W Conn. 4P HDR ASSEMBL

TE Part #2-2338245-8
EP2.5 HDR 8P VERT BOSS,BLUE,UL

TE Part #826652-3
3P AMPMODU II STIFT LEI

TE Part #1-2301994-4
RJ45 JACK INT.MAG. 1GB LED 1X1 INV.



Documents

Product Drawings

AMP POWER D/LOCK T/HDR ASSY 6P

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_179841-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_179841-1_E.3d_stp.zip

English

Customer View Model

ENG_CVM_179841-1_E.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_179841-1_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_179841-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_179841-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Engineering Report

English



Instruction Sheets

Instruction Sheet (non U.S.)

English

AMP POWER DOUBLELOCK CONNECTOR SERIES

English

Agency Approvals

CSA Certificate

English