



GRACE INERTIA 2.5

TE Internal #: 8-1971793-1  
Housing, Plug, Wire-to-Wire, 8 Position, 2.5 mm [.098 in] Centerline,  
Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, GRACE  
INERTIA 2.5

[View on TE.com >](#)

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings >  
Glow Wire Sig GRACE INERTIA Plug



Connector Product Type: **Housing**  
Connector & Housing Type: **Plug**  
Connector System: **Wire-to-Wire**  
Number of Positions: **8**  
Centerline (Pitch): **2.5 mm [ .098 in ]**

[All Glow Wire Sig GRACE INERTIA Plug \(20\)](#)

Features

Product Type Features

|                                   |              |
|-----------------------------------|--------------|
| Connector Product Type            | Housing      |
| Connector & Housing Type          | Plug         |
| Connector System                  | Wire-to-Wire |
| Sealable                          | No           |
| Connector & Contact Terminates To | Wire & Cable |

Configuration Features

|                     |   |
|---------------------|---|
| Number of Positions | 8 |
| Number of Rows      | 1 |

Electrical Characteristics

|                   |        |
|-------------------|--------|
| Operating Voltage | 50 VAC |
|-------------------|--------|

Body Features

|  |  |
|--|--|
|  |  |
|--|--|



|                         |         |
|-------------------------|---------|
| Connector & Keying Code | A       |
| Primary Product Color   | Natural |

Contact Features

|                                  |              |
|----------------------------------|--------------|
| Contact Retention Within Housing | Without      |
| Contact Layout                   | Inline       |
| Contact Type                     | Tab          |
| Contact Base Material            | Copper Alloy |
| Contact Current Rating (Max)     | 3 A          |

Termination Features

|                                    |       |
|------------------------------------|-------|
| Termination Method to Wire & Cable | Crimp |
|------------------------------------|-------|

Mechanical Attachment

|                         |                            |
|-------------------------|----------------------------|
| Strain Relief           | Without                    |
| Panel Mount Feature     | Without                    |
| PCB Mount Retention     | Without                    |
| Mating Retention Type   | Latch                      |
| Mating Retention        | With                       |
| Connector Mounting Type | Cable Mount (Free-Hanging) |

Housing Features

|                             |                  |
|-----------------------------|------------------|
| Housing Entry Configuration | Both Ends Closed |
| Housing Material            | PA 66 GF         |
| Centerline (Pitch)          | 2.5 mm [.098 in] |

Dimensions

|                  |                   |
|------------------|-------------------|
| Connector Length | 20.7 mm [.814 in] |
| Connector Height | 5.88 mm [.231 in] |
| Wire Size        | .081 – .326 mm²   |

Usage Conditions

|                             |                             |
|-----------------------------|-----------------------------|
| Operating Temperature Range | -30 – 105 °C [-22 – 221 °F] |
|-----------------------------|-----------------------------|

Operation/Application

|                     |                |
|---------------------|----------------|
| Circuit Application | Power & Signal |
|---------------------|----------------|

Industry Standards

|                        |           |
|------------------------|-----------|
| Glow Wire Rating       | Glow Wire |
| UL Flammability Rating | UL 94V-0  |



Packaging Features

|                    |           |
|--------------------|-----------|
| Packaging Quantity | 400       |
| Packaging Method   | Bag & Box |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Not reviewed for solder process capability                                                                                      |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 8-2232546-1  
GI2.5 HDR ASS 8P NC NO BOSS TAPE



TE Part # 8-1971794-2  
GI2.5 TPA,8P

Also in the Series | GRACE INERTIA 2.5



|                                  |                                                   |                                |                                    |
|----------------------------------|---------------------------------------------------|--------------------------------|------------------------------------|
|                                  |                                                   |                                |                                    |
| Connector Contacts(6)            | Connector Hardware(7)                             | PCB Headers & Receptacles(138) | Rectangular Connector Housings(49) |
|                                  |                                                   |                                |                                    |
| Rectangular Power Connectors(35) | Wire-to-Board Connector Assemblies & Housings(46) |                                |                                    |

Customers Also Bought

|                                                            |                                                              |                                                      |                                                          |
|------------------------------------------------------------|--------------------------------------------------------------|------------------------------------------------------|----------------------------------------------------------|
|                                                            |                                                              |                                                      |                                                          |
| TE Part #5748979-1<br>AMP III RCPT 9P RA 318 FFSCRLK /BDLK | TE Part #1971795-1<br>NEW GI CONN2.5 REC. CONTACT            | TE Part #4-2176230-2<br>3522 2K2 5% 3W               | TE Part #8-1971793-2<br>Glow Wire Sig GRACE INERTIA Plug |
|                                                            |                                                              |                                                      |                                                          |
| TE Part #5104338-3<br>A/L LOW PRO HDR 16P VERT HT          | TE Part #4-1971798-1<br>NEW GI CONN2.5 HDR ASMBLY 4P NC D1.0 | TE Part #1838274-3<br>M12 Fld Ser CONN. Female Skt S | TE Part #5104338-2<br>A/L LOW PRO HDR 14P VERT HT        |

Documents

Product Drawings  
NEW GI CONN2.5 PLUG HSG 8P NC

English

- CAD Files
- 3D PDF
- 3D
- Customer View Model
- ENG\_CVM\_CVM\_8-1971793-1\_J.2d\_dxf.zip



English

Customer View Model

[ENG\\_CVM\\_CVM\\_8-1971793-1\\_J.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_8-1971793-1\\_J.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[5-1773465-3-GI2.5Flyer](#)

English

[7-1773465-8-GI2.5-ChineseFlyer](#)

Product Specifications

[Product Specification](#)

English