

Specification Sheet

Part Number: SAOM820HIRHSH1



Axial Oval Mount, .31" (8mm) Mounting Hole, PA66HIRHSUV, Black, 500/pkg

Article Number	151-29701
Type	SAOM82
Color	Black (BK)
Features & Benefits	• Positions bundles off cross members and frame rails to prevent abrasion and chafing. • Metal insert bushing accommodates high torque installation. • Made with high impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.
Quantity Per	bag
Product Description	HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.
Short Description	Axial Oval Mount, .31" (8mm) Mounting Hole, PA66HIRHSUV, Black, 500/pkg

Global Part Name	SAOM82-PA66HIRHSUV-BK
Length L (Imperial)	1.40
Length L (Metric)	34.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	1.0
Width W (Metric)	26.0
Cable Ties	T50 - T250
Height H (Imperial)	1.40
Height H (Metric)	35.0
Cable Tie Width Max (Imperial)	0.5
Cable Tie Width Max (Metric)	12.7
Mounting Hole Diameter D (Imperial)	0.31
Mounting Hole Diameter D (Metric)	8.0 mm
Mounting Hole Diameter D Min (Imperial)	0.31
Mounting Hole Diameter D Max (Imperial)	0.31
Mounting Hole Diameter D Max (Metric)	8.0
Stud Diameter (Metric)	8.0 mm

Stud Diamater (Imperial)	0.3125
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	10.8

