


Series 511

Molded Unshielded RF Coils



Physical Parameters

	Inches	Millimeters
Length	0.375 ± 0.010	9.53 ± 0.25
Diameter	0.156 ± 0.010	3.96 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

Phenolic 35°C Rise
Iron 15°C Rise

Operating Temperature Range

Phenolic -55°C to +125°C;
Iron -55°C to +105°C

Maximum Power Dissipation at 90°C

Phenolic 0.312 W
Iron 0.134 W

Weight Max. (Grams) 0.9

Packaging Tape & reel: 12" reel, 2500 pieces max.;
14" reel, 4000 pieces max. For additional packaging
options, see page 146.

Made in the U.S.A.

PART NUMBER

INDUCTANCE
(µH) ± 5%

Q MINIMUM

TEST FREQUENCY (MHz)

SRF MINIMUM (MHz)

DC RESISTANCE
MAXIMUM (OHMS)

CURRENT RATING
MAXIMUM (mA)

SERIES 511 PHENOLIC CORE

511-2J	0.16	50	25.0	525	0.040	2370
511-3J	0.18	50	25.0	500	0.043	2285
511-4J	0.20	50	25.0	475	0.047	2185
511-6J	0.24	45	25.0	415	0.060	1935
511-7J	0.27	45	25.0	400	0.070	1790
511-8J	0.30	45	25.0	380	0.080	1675
511-10J	0.36	45	25.0	345	0.098	1515
511-11J	0.39	45	25.0	330	0.100	1500
511-12J	0.43	45	25.0	315	0.110	1430
511-14J	0.51	45	25.0	300	0.130	1315
511-16J	0.62	50	25.0	260	0.140	1265
511-18J	0.75	50	25.0	230	0.180	1115
511-20J	0.91	50	25.0	210	0.240	970
511-22J	1.10	33	7.9	190	0.420	730
511-24J	1.30	33	7.9	170	0.480	685
511-26J	1.60	33	7.9	155	0.600	610
511-28J	2.00	33	7.9	140	0.800	530
511-30J	2.40	33	7.9	130	1.100	450
511-32J	3.00	33	7.9	115	1.800	355
511-34J	3.60	33	7.9	105	2.150	325
511-36J	4.30	33	7.9	95	2.400	305

SERIES 511 IRON CORE

511-38J	5.10	35	7.9	65	0.360	570
511-40J	6.20	45	7.9	60	0.470	455
511-42J	7.50	50	7.9	55	0.550	420
511-44J	9.10	55	7.9	50	0.800	350
511-46J	11.0	60	2.5	44	1.050	310
511-48J	13.0	65	2.5	40	1.200	285
511-50J	16.0	70	2.5	38	1.800	230
511-52J	20.0	75	2.5	30	2.500	195

Optional Tolerances: H = 3% G = 2% F = 1%