



PennEngineering
Corporate Headquarters – Danboro, PA

5190 Old Easton Rd.

Danboro, PA 18916

Phone: 215-766-8853

Toll-Free Phone: 1-800-237-4736 (U.S. only)


Email: info@pemnet.com

Website: www.pemnet.com

Part # SL-M3.5-1ZI, TRI-DENT® Locknuts - Type SL - Metric


Type SL self-locking nuts are designed with a unique and economical TRI-DENT® locking feature, which meets demanding locking performance requirements.

- 3 cycle locking performance. Achieved using steel socket head cap screws, 180 ksi / property



Specifications

Thread Size x Pitch	M3.5 x 0.6
Thread Code	M3.5
Shank Code	1
	0.98 mm
A (Shank) Max.	
Min. Sheet Thickness	1 mm
Hole Size in Sheet + 0.08	4.75 mm
C Max.	4.73 mm
E ± 0.25	7.11 mm
T ± 0.25	1.5 mm
Min. Dist. Hole C/L to Edge	5.6 mm
For Use in Sheet Hardness	HRB 80 / HB 150 or less
Thread Specification	Internal, ASME B1.13M, 6H
Fastener Material	Heat-Treated Carbon Steel



Standard Finish	Zinc plated per ASTM B633,	SC1 (5µm), Type III, colorless
CAD Supplier	PennEngineering® (PEM®)	