



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#)

**Text Search: 'HSTT12-48-TLC'**

Your search criteria matched only one product, shown below

## HSTT12-48-TLC



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets Mil Spec AMSDTL-23053/5 Class 1(Colors), Class 2 (Clear)

|                                        |                                                                   |
|----------------------------------------|-------------------------------------------------------------------|
| Part Number                            | HSTT1248-TLC                                                      |
| RoHS Compliancy Status                 | Compliant                                                         |
| Part Description                       | Thin Wall Polyolefin Heat Shrink                                  |
| Material                               | Flame retardant polyolefin cross-linked except clear <sup>^</sup> |
| Color                                  | Clear                                                             |
| Military Specification                 | AMS-DTL-23053/5 Class 2                                           |
| Length (ft.)                           | 4                                                                 |
| Length (m)                             | 1.2                                                               |
| CE Compliant                           | No                                                                |
| CE Marking                             | No                                                                |
| Max. Recovered I.D. (In.)              | .062                                                              |
| Max. Recovered I.D. (mm)               | 1.6                                                               |
| Min. Expanded I.D. (In.)               | .125                                                              |
| Min. Expanded I.D. (mm)                | 3.2                                                               |
| Nominal Diameter / Size                | .125                                                              |
| Nominal Recovered Wall Thickness (In.) | .020                                                              |
| Nominal Recovered Wall Thickness (mm)  | .5                                                                |
| Pricing Description                    | Heat Shrink Thin, .12"(3.2mm) Dia, Clear                          |
| Shrink Ratio                           | 2:1                                                               |
| Temperature Range                      | -67°F to 275°F (-55°C to 135°C)                                   |
| Min. Order UOM                         | PC                                                                |
| Min. Order Qty.                        | 250                                                               |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>                                    |
| Add to Favorite Product List           |                                                                   |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.