




Technical Data

Labels for component marking, laser printer  
Helatag 1101 (White)

22.01.2024

TAG171LA4-1101-WH  
Article Number 594-11015



Material: Type 1101, Polyester, white (1101)  
Colour: White (WH)

Operating Temperature : -40 °C to +150 °C  
Curing Temperature: from 0 °C

Self adhesive (Yes/No): Yes

Width (W): 210.00 mm  
Height (H): 297.00 mm  
Width of Liner (WL): 210.00 mm  
Labels per Row: 1 pc.  
Labels per Sheet: 1 pc.

Thickness of Foil: 55 µm  
Thickness of Adhesive (TA) nom.: 24 µm

Test Method  
ISO 534

Adhesive: Acrylic  
Initial tack: 13 N  
Shear strength: 1000 min

FINAT FTM 9  
FINAT FTM 8

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved



## Technical Data

22.01.2024

Labels for component marking, laser printer  
Helatag 1101 (White)

Print Method:

laser print

Shelf Life:

Minimum 1 year upon receipt / maximal 4 years after production date.

Storage Temperature:

+15 °C to +25 °C

Storage conditions:

45%  $\pm$ 5% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness., Must be stored in a dark place.

Application Method:

The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.



We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved