

Connector Saver

.050"


9 thru 100 Contacts


Rugged Metal


MM


Rugged Plastic

MN










RECEPTACLE

PLUG



DIMENSIONS							
	CONTACT		В				
SIZE	ROWS	A	PLUG MAX	RCPT MAX	D	H	HARDWARE
9	2	.775	.334	.400	.565	.298	#2-56 UNC THD (.092 DIA THRU)
15		.925	.484	.550	.715		
21		1.075	.634	.700	.865		
25		1.175	.734	.800	.965		
31		1.325	.884	.950	1.115		
37		1.475	1.034	1.100	1.265		
51**		1.825	1.384	1.450	1.615		
51	3	1.425	.984	1.050	1.215	.341	
69***		1.725	1.284	1.350	1.515		
100	4	2.160	1.384	1.508	1.800	.384	#4-40 UNC THD (.147 DIA THRU)

^{** = 2} ROW, 51 POSITION CONNECTORS ARE AVAILABLE IN METAL ONLY (NON MIL-SPEC INTERFACE)

^{*** = 69} POSITION CONNECTORS ARE AVAILABLE IN METAL ONLY.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AirBorn:

MM-212-031-143-0000-93A