



Terminals & Splices > Splices



Splice Type: **Parallel Splice**
Wire Size: **1.25 – 2 mm²**
Sealable: **No**
Splice Features: **Serrated**

Features

Product Type Features

Splice Accessory Type	Splice
Style Code	B
Splice Type	Parallel Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Product Weight	.384 g
Splice Features	Serrated
Primary Product Color	Orange

Contact Features

	300 μin
--	---------



Terminal Plating Material	Nickel
Contact Base Material	Nickel
Barrel Type	Closed

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Outside Diameter	4.19 mm[.165 in]
Wire Size	2050 – 5180 CMA
Barrel Inside Diameter	2.16 mm[.085 in]
Terminal Material Thickness	.76 mm[.03 in]
Product Length	7.35 mm[.301 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	649 °C[1200 °F]

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

REPRESENTATION ONLY

TE Part # 46447
DAHT STRATO 22-10 ASSY

Customers Also Bought

TE Part #325148
PIDG RECT 22-16COMM 22-18MIL 2

TE Part #4-1625984-6
HSA50 2R5 5%

TE Part #1-104481-2
SHORT POINT RECP CONT LP

TE Part #34322
SPLICE,SOLIS BUTT 6

TE Part #2-35775-1
TERMINAL,SOLIS R 16-14HD 1/4

TE Part #1-51864-1
TERMINAL,PIDG R IR 14 8

TE Part #36909
SPLICE,SOLIS PARA 3/0

TE Part #1-1393127-2
PRD-11AG0-240=PRD



Documents

Product Drawings

SPLICE,SOLIS PARA HT 16-14

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_322347_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_322347_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_322347_F.3d_stp.zip

English

Customer View Model

ENG_CVM_322347_G.3d_igs.zip

English

Customer View Model

ENG_CVM_322347_G.3d_stp.zip

English

Customer View Model

ENG_CVM_322347_G.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

Instruction Sheets

Instruction Sheet (U.S.)

English



AMP Multiple-Wire Post-Insulated STRATO-THERM Splice Caps

English