



























3 PLATING IN CONTACT AREA PRODUCT NUMBER NOTES: DASH NUMBER PERFORMANCE LEVEL NOTES 89075-XYY I. FOR DIM A AND B SEE SHEET 2 AND UP. OR -AYY OR -AYYY TELCORDIA CO SEE NOTE 8 2. BODY MATERIAL: LIQUID CRYSTAL 89075-XYYY -NIYY OR -NIYYY TELCORDIA CO (NXT) POLYMER 30 % GLASS. 89075-XYYLF Α -IYY OR -IYYY TELCORDIA CO FLAME RETARDANT ACC. UL 94-VO. OR -2YY OR -2YYY TELECOM CLASS 89075-XYYYLF 3. PIN MATERIAL: PHOSPHOR BRONZE IEC CLASS I -3YY OR -3YYY 4. PLATING ON PRESS-FIT TAIL: 89075-XYY IS SnPb -N5YY OR -N5YYY TELCORDIA UE (NXT) 89075-XYYLF IS SN (LEAD FREE) PLATING ON CONTACT AREA CONFORMS TO PERFORMANCE -5YY OR -5YYY TELCORDIA UE LEVEL SHOWN IN TABLE. -AYYLF OR -AYYYLF TELCORDIA CO SEE NOTE 10 5. PRODUCT MARKING: TELCORDIA CO (NXT) PART NUMBER DESIGNATION & BATCH I.D. -NIYYLF OR -NIYYYLF SEE NOTE 10 IEC CLASS I 6. ALL PRODUCTS WITH PART NUMBERS SHOWN IN TELCORDIA CO -IYYLF OR -IYYYLF SEE NOTE 10 IEC CLASS I SUBSEQUENT TABLES WILL BE PACKAGED IN TUBES. IF TRAY PACKAGING IS REQUIRED, A SUFFIX "P" -2YYLF OR -2YYYLF TELECOM CLASS SEE NOTE 10 WILL BE ADDED TO THE END OF THE PART NUMBER EXAMPLE: XXXXX-XXXP OR XXXXX-XXXXP, -N5YYLF OR -N5YYYLF TELCORDIA UE (NXT) SEE NOTE 10 XXXXX-XXXPLF OR XXXXX-XXXXPLF -5YYLF OR -5YYYLF TELCORDIA UE SEE NOTE 10 7. PRODUCT SPECIFICATION GS-12-180 APPLICATION SPECIFICATION BUS-20-073 -A PLATING HAS AU FLASH IN PRESS FIT AREA (LEAD FREE). AFTER INSERTION INTO CIRCUIT BOARD WITH QUALIFIED TOOL. THE PRODUCTS WHERE THE PART NUMBER ENDS IN LF MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008. ALL PRODUCTS EXCEPT THOSE WITH PART NUMBERS CONTAINING (DRAWING NO.)-NI--- OR (DRAWING NO.)-N5---WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN. PART NUMBERS (DRAWING NO.)-NI---AND (DRAWINGS NO.)-N5---WILL NOT WITHSTAND REFLOW AND AU CONTACT SURFACE OF THE CONTACTS SHALL BE EXPOSED TO A MAXIMIM 140°C FOR NO LONGER THAN 15 SECONDS IN A WAVE SOLDER APPLICATION. FOR LEAD FREE PART NUMBERS. ADD AN "LF" SUFFIX. EXAMPLE:89075-X01LF dr **Terran Huang** 2010/07/08 scale spec ref projection size mm A 4 tolerance std Andy Lu 2012/03/08 2:1 eng TOLERANCES UNLESS Thian-Zhao Lin 2012/03/12 ELX-DG-010531-1 chr ecn no OTHERWISE SPECIFIED ASME YI4.5 D **Pei-Ming Zheng** 2012/03/12 METRAL rel level product family appr Released 0.X  $\pm 0.3$ 0 rev METRAL SIGNAL HEADER 89075  $\pm 0.13$ surface 1200 inear 0.XX D \$  $\pm 0.051$ CE 4 MOD, 4 ROW PRESS-FIT 0.XXX 0°  $\pm 2^{\circ}$ ASME YI4.5 angular |www.fci.com| cat. no. Product - Customer Drw sheet 15 of 15 Pro/E File - REV C - 2009-06-09 PDS: Rev:CE STATUS:Released Printed: Mar 12, 2012