

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B10, with double locking latch, material: Die-cast aluminum, salt water resistant, variable, height: 57 mm, cable gland: none, Standard, Without thread opening for screw connection

## Product description

Sleeve housing, without screw thread

## Your advantages

- Good shielding in the event of electromagnetic interference

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1420034             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF56                |
| Product key                          | BF7APB              |
| Catalog page                         | Page 614 (C-2-2019) |
| GTIN                                 | 4055626201382       |
| Weight per piece (including packing) | 179.5 g             |
| Weight per piece (excluding packing) | 179.5 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | CN                  |

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>

## Technical data

### Notes

|         |                                                                                          |
|---------|------------------------------------------------------------------------------------------|
| General | for contact inserts HC-B10, BB18, DD42, M, K8/24, HV03                                   |
| General | also available as a powder-coated or color version: 1372776 HC-STA-B10-HLWD-BLANK-EL/... |


### Product properties

|                     |                            |
|---------------------|----------------------------|
| Product type        | Housing with locking latch |
| Housing type        | Sleeve housing             |
| Application         | Standard                   |
| Type                | B10                        |
| Type                | Low design                 |
| Cable outlet        | variable                   |
| Pg screw connection | none                       |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 02 |
|------------------|----|

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 44 mm                                                                                |
| Height              | 57 mm                                                                                |
| Length              | 73 mm                                                                                |

### Material specifications

|                                        |                                         |
|----------------------------------------|-----------------------------------------|
| Flammability rating according to UL 94 | V0 (Interlock)                          |
| Housing material                       | Die-cast aluminum, salt water resistant |
| Housing surface material               | uncoated                                |
| Locking latch material                 | PA                                      |

### Mechanical properties

#### Mechanical data

|              |       |
|--------------|-------|
| Locking type | Latch |
|--------------|-------|

### Mounting

|             |    |
|-------------|----|
| Thread type | () |
|-------------|----|

### Environmental and real-life conditions

#### Ambient conditions

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection            | IP66              |
|                                 | IP67              |
| Enclosure rating (NEMA)         | 4 (UL 50e)        |
|                                 | 4X (UL 50e)       |
|                                 | 12 (UL 50e)       |
| Impact strength                 | IK09              |
| Ambient temperature (operation) | -40 °C ... 125 °C |

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>



## Drawings

Dimensional drawing



Dimensional drawing

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1420034>

### DNV

Approval ID: TAE000037S



### EAC

Approval ID: RU C-DE.AI30.B.01102



### EAC

Approval ID: RU C-DE.BL08.B.00511

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing



1420034

<https://www.phoenixcontact.com/us/products/1420034>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440202 |
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# HC-STA-B10-HLWD-BLANK-EL-AL - Housing

1420034

<https://www.phoenixcontact.com/us/products/1420034>



## Accessories

### US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/us/products/0830085>

Plastic label, Card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



---

### HC-B10-HCFD-PR-BK - Protective cover

1346529

<https://www.phoenixcontact.com/us/products/1346529>

Protective cover B10, for double locking latch, protective cover material: PC, height: 26.3 mm, seal: yes





# HC-STA-B10-HLWD-BLANK-EL-AL - Housing

1420034

<https://www.phoenixcontact.com/us/products/1420034>



## US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/us/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)