

GlobalMark®2 Label Materials

BradyID.com/globalmark

Pre-Printed Pre-Cut Blank Sign Headers (B-595)

For creating Arc Flash and safety warning labels in seconds.

- Allows printer to create multicolor signs fast - in a single print pass
- Headers meet NFPA 70E, OSHA 1910.145 and ASME/ANSI Z535 standards
- Indoor/outdoor grade material conforms to rough, highly textured, and "difficult to adhere to" surfaces

Service temp: -40°F to 180°F Application temp: 0°F to 180°F
Average Outdoor Durability: 8-10 years




Figure 73



Print your own valve tag!
View page 400 for blank rigid valve tags!

NOTE: A free firmware upgrade to version 25i for your GlobalMark® Label Maker is required to print these supplies. Contact Brady Technical Support at 1-800-643-8766 to upgrade.

Diagram	Catalog #	B#	Header	Label Height A Inch (mm)	Label Width B Inch (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
Fig. 73	121550	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121558	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121552	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121560	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121551	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121559	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121549	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121557	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121553	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121561	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121554	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121562	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121563	B-595		1.125 (28.6) *	2.750 (69.8)	1	300	76739
Fig. 73	121547	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121564	B-595		2.250 (57.5) *	3.750 (95.2)	1	250	76739
Fig. 73	121555	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739
Fig. 73	121548	B-595		2.250 (57.5)	3.250 (82.6)	1	270	76739
Fig. 73	121556	B-595		4.000 (101.6)	6.250 (158.8)	1	165	76739

*Pre-sized to fit blank rigid valve tags (page 400) but can also be used on its own as general purpose label.
Visit BradyID.com for information on Valve Tag Kit (catalog #142133).

Non-Adhesive Pre-Printed & Pre-Cut Safety Tags (B-551)

Pre-printed and pre-cut to save you time!

- Non-adhesive semi rigid card stock
- Tags are pre-cut with hole and chamfered corners
- Perforated between tags
- Snap-in plastic grommets available for extra strength around mounting hole

Service temp: -40°F to 180°F Application temp: 0°F to 180°F
Average Outdoor Durability: 8-10 years




Figure 69



Diagram	Catalog #	B#	Header	Tag Width A Inch (mm)	Tag Height B Inch (mm)	Tags Per Row	Tags Per Roll	Rec. Ribbon
Fig. 69	121543	B-551		3.250 (82.6)	5.750 (146.1)	1	100	76739
Fig. 69	121544	B-551		3.250 (82.6)	5.750 (146.1)	1	100	76739
Fig. 69	121545	B-551		3.250 (82.6)	5.750 (146.1)	1	100	76739
Fig. 69	121546	B-551		3.250 (82.6)	5.750 (146.1)	1	100	76739

NOTE: A free firmware upgrade to version 25i for your GlobalMark® Label Maker is required to print these supplies. Contact Brady Technical Support at 1-800-643-8766 to upgrade.

View all GlobalMark® Print Ribbon parts on page 389.