



Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO
Q1


A
B
C
D
E
F

12345678

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	1	DIS-E-3269	E.M	H.T	96.11.12	△					. .
△	2	DIS-E-000197	Y.S	Y.E	05.08.29	△					. .
△						△					. .



△ NOTE 1 REF.NO.3 RETENFORCE TO BE 100N MIN AT DIRECTION A.



4	PBT	UL94V-0 (BLACK)			
3	PBT	UL94V-0 (BLACK)	7	PBT	UL94V-0 (BLACK)
2	BERYLIUM COPPER	CONTACT AREA:GOLD PLATED IDC AREA:GOLD FLASH PLATING △	6	PBT	UL94V-0 (BLACK)
1	BERYLIUM COPPER	CONTACT AREA:GOLD PLATED IDC AREA:GOLD FLASH PLATING △	5	STEEL	NICKEL PLATED
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	M.NAKAMURA	M.NAKAMURA	S.KIKUTA	A.NAKAZAWA	
	90.03.14	90.03.14	90.03.14	90.03.14	. .

SCALE 2 : 1	DRAWING NO. EDC3-040393	PART NO. DX30AM-100P
UNITS mm	HRS HIROSE ELECTRIC CO., LTD	CODE NO. CL230-5031-0

1/1

12345678 FORM NO.229