





features

- Semi-precision metal film resistors
- Meets requirements of MIL-R-22684
- Suitable for automatic machine insertion
- MFS two times the power rating of the standard body type
- Marking: Blue-gray body color with color-coded bands
- Products with lead-free terminations meet EU RoHS and China RoHS requirements
- AEC-Q200 Qualified: MF1/4, MFS1/4, MFS1/2


dimensions and construction




Type	Dimensions inches (mm)				
	L (ref.)	C (max.)	D	d (nom.)	I*
MFS1/4	.126±.008 (3.2±0.2)	.133 (3.4)	.066 ^{+.007} _{-.004} (1.7 ^{+0.2} _{-.01})	.018 (0.45)	1.10±.118 (28.0±3.0)
MF1/4	.248±.02 (6.3±0.5)	.280 (7.1)	.091±.012 (2.3±0.3)	.024 (0.6)	
MFS1/2	.248±.02 (6.3±0.5)	.280 (7.1)	.091±.012 (2.3±0.3)	.024 (0.6)	
MF1/2	.354±.04 (9.0±1.0)	.437 (11.1)	.138±.016 (3.5±0.4)	.024 (0.6)	
MF1	.610±.02 (15.5±0.5)	.721 (18.3)	.217±.02 (5.5±0.5)	.031 (0.8)	1.50±.118 (38.0±3.0)
RK1/4	.248±.02 (6.3±0.5)	.280 (7.1)	.091±.012 (2.3±0.3)	.024 (0.6)	0.94 min. (24.0 min.)
RK1/2	.374±.04 (9.5±1.0)	.437 (11.1)	.138±.016 (3.5±0.4)	.024 (0.6)	
RK1	.610±.04 (15.5±1.0)	.720 (18.3)	.217±.02 (5.5±0.5)	.031 (0.8)	

* Lead length changes depending on taping and forming.

Derating Curve



Surface Temperature Rise



ordering information

New Part #	MF	1/4	L	C	T52	R	R20	J
Type	MF MFS RK	Power Rating 1/4: 0.25W 1/2: 0.50W 1: 1W	T.C.R. E: ±25 C: ±50 D: ±100 L: ±200 G: ±250 B: ±350	Termination Material C: SnCu	Taping and Forming 1/4: T26, T52, VT, VTP, VTE, MT, M, U, M10, M12.5 1/2: T26, T52, VTP, VTE, M12.5, M15 1: T521	Packaging A: Ammo R: Reel	Nominal Resistance +2%: 2 significant figures + 1 multiplier +0.5%, +1%: 3 significant figures + 1 multiplier "R" indicates decimal on value <100Ω	Tolerance B: ±0.1% C: ±0.25% D: ±0.5% F: ±1% G: ±2% J: ±5%

For further information on packaging, please refer to Appendix C.

applications and ratings

Part Designation	Power Rating @ 70°C	Minimum Dielectric Withstanding Voltage	T.C.R. (ppm/°C)	Resistance Range (Ω)						Absolute Maximum Working Voltage	Absolute Maximum Overload Voltage	Operating Temperature Range
				(B±0.1%) E-96	(C±0.25%) E-96	(D±0.5%) E-24 E-192	(F±1.0%) E-24 E-96	(G±2.0%) E-24	(J±5.0%) E-24			
MFS1/4C	0.25W	300V	C: ±50	—	—	49.9 - 562k	10 - 1M	—	—	250V	500V	-55°C to +155°C
MFS1/4D			D: ±100	—	—	—	—	—	—			

applications and ratings (continued)

Part Designation	Power Rating @ 70°C	Minimum Dielectric Withstanding Voltage	T.C.R. (ppm/°C)	Resistance Range (Ω)						Absolute Maximum Working Voltage	Absolute Maximum Overload Voltage	Operating Temperature Range
				(B±0.1%) E-96	(C±0.25%) E-96	(D±0.5%) E-24 E-192	(F±1.0%) E-24 E-96	(G±2.0%) E-24	(J±5.0%) E-24			
MF1/4C	0.25W	500V	C: ±50	—	—	10- 2.21M	10 - 2.21M	—	—	250V	500V	-55°C to +155°C
MF1/4D			D: ±100	—	—			—				
MF1/4L			L: ±200	—	—	—	1.0 - 10	0.51 - 10				
MFS1/2C	0.50W	500V	C: ±50	—	—	10 - 1M	10 - 2.21M	10 - 2.2M	—	350V	700V	
MFS1/2D			D: ±100									
MF1/2C	0.50W	700V	C: ±50	—	—	10 - 5.05M	10 - 4.99M	—	—	350V	700V	
MF1/2D			D: ±100	—	—		10 - 5.11M					
MF1/2L			L: ±200	—	—	—	1.0 - 10					
MF1C	1W	700V	C: ±50	47.5 - 1.0M	47.5 - 2.49M	10 - 5.11M	1.0 - 6.81M	—	—	350V	700V	
MF1D			D: ±100	—	—			—				
MF1E			E: ±25	47.5 - 1.0M	47.5 - 2.49M	47.5 - 4.64M	47.5 - 5.11M	—				
RK1/4D	0.25W	500V	D: ±100	—	—	—	3.09M - 25M	—	—	500V	700V	
RK1/4L			L: ±200	—	—	—	—	3.3M - 33M	3.3M - 33M			
RK1/4B			B: ±350	—	—	—	100k - 25M	100k - 33M	100k - 33M			
RK1/2D	0.50W	700V	D: ±100	—	—	—	5.11M - 33M	—	—	700V	1000V	
RK1/2L			L: ±200	—	—	—	—	6.2M - 33M	6.2M - 33M			
RK1/2B			B: ±350	—	—	—	100k - 35M	100k - 51M	100k - 51M			
RK1BC	1W	1000V	B: ±350	—	—	—	100k - 51M	100k - 100M	100k - 100M	1000V	1500V	
RK1/2G*	0.50W	700V	G: ±250	—	—	—	—	—	1M - 12M	350V	700V	

* Discharge path resistor

environmental applications

Performance Characteristics

Parameter	Requirement $\Delta R \pm (\% + 0.05\Omega)$	Limit	Typical	Test Method
Resistance	Within specified tolerance	—	—	25°C
T.C.R.	Within specified T.C.R.	—	—	Room temperature, +100°C, RK: +25°C/+125°C
Overload (Short Time)	RK: ±1%, RK1/2G: ±2.5% MF: ±0.5%	RK: ±0.6%, RK1/2G: ±1% MF: ±0.3%	—	Rated voltage x 2.5 or max. overload voltage for 5 seconds, whichever is less; MFS1/2: Rated voltage x 2 or max. overload voltage for 5 seconds, whichever is less
Resistance to Solder Heat	RK: ±1%; RK1/2G: ±5%; MFS: ±0.75%; MF1/4, MFS1/2, MF1/2: ±0.5%	RK: ±0.5%; RK1/2G: ±1% MFS1/4: ±0.4%; MF1/4, MFS1/2, MF1/2: ±0.25%	—	260°C ± 5°C, 10 seconds ± 1 second or 350°C ± 10°C, 3.5 seconds ± 0.5 second
Dielectric Withstanding Voltage	No breakdown	—	—	1 minute
Insulation Resistance	Not less than 10,000MΩ	—	—	100V, 1 minute
Rapid Change of Temperature	RK,MF: ±1%; RK1/2G: ±5%	MF: ±0.3%; RK: ±0.5%, RK1/2G: ±1%	—	-55°C (30 minutes), +155°C (30 minutes), 5 cycles
Moisture Resistance	RK: ±5%; RK1/2G: ±10%; MFS1/4: ±1.5%; MF1/4, MFS1/2, MF1/2: ±1%	RK: ±2%; RK1/2G: ±5%; MFS1/4: ±1%; MF1/4, MFS1/2, MF1/2: ±0.75%	—	40°C ± 2°C, 90 - 95% RH, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
Endurance at 70°C	RK: ±5%; RK1/2G: ±10%; MFS1/4: ±1.5%; MF1/4, MFS1/2, MF1/2: ±1%	RK: ±2%; RK1/2G: ±5%; MFS1/4: ±1%; MF1/4, MFS1/2, MF1/2: ±0.75%	—	70°C ± 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
Resistance to Solvent	No abnormality in appearance. Marking shall be easily legible	—	—	The resistor shall be immersed for 5 seconds in IPA
Impulse	No such abnormalities as short-circuit, burnout, breakdown, etc.	—	—	Discharge from 1000pF capacitor 50 pulses. Internal 2.5 seconds. Charge voltage: 1.25kV (RK1/4), 2.5kV (RK1/2) and 6kV (RK1)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KOA Speer:

[MFS1/4DLT52R1004F](#) [MF1/4CLT52R4992F](#) [MF1/2DLT52R2213F](#) [MF1/2DLT52R2212F](#) [MF1/2CLT52R2201F](#)
[MF1/4DL3324F](#) [MF1/4CLT52R4990F](#) [MF1/4DL33R2F](#) [MF1/4CL33R2F](#) [MF1/4DL3163F](#) [MF1/4CL3322F](#)
[MF1/4DLT52R1152F](#) [MF1/4CL3321F](#) [MF1/4DL3322F](#) [MF1/4DL3162F](#) [MF1/4DL3161F](#) [MF1/4DLT52R1151F](#)
[MF1/2DL3162F](#) [MF1/2CL3162F](#) [MF1/2DL3321F](#) [MF1/2DL33R2F](#) [MF1/2DL3322F](#) [MF1/2CL3321F](#) [MF1/2CL33R2F](#)
[MF1/4CL3162F](#) [MF1/2CL3322F](#) [MF1/2CLT52R1473F](#) [MF1/2DLT52R2493F](#) [MF1/2DL2801F](#) [MF1/4DLT52R4750F](#)
[MF1/4DLT52R4752F](#) [MF1/4DLT52R4751F](#) [MF1/2DL2210F](#) [MF1/2CL2210F](#) [MF1/4DLT52R4754F](#) [MF1/4CL2210F](#)
[MF1/4CL2801F](#) [MF1/2CLT52R5101F](#) [MF1/4DL2R20F](#) [MF1/4DL2210F](#) [MF1/2CLT52R6982F](#) [MFS1/4DLT52R1001F](#)
[MF1/4CL2214F](#) [MF1/2CL2214F](#) [MF1/4DL2801F](#) [MFS1/4DLT52R1002F](#) [MF1/4DCT52R3011F](#) [MF1/2DL2214F](#)
[MF1/4DL2214F](#) [MF1/4DLT52R4753F](#) [MF1/2CLT52R6980F](#) [MF1/2CLT52R6981F](#) [MF1/4DLT26A4642F](#)
[MFS1/4DLT52R1003F](#) [MF1/4DLT52R1R00F](#) [MF1/2CL2801F](#) [MF1/2DLT52R2491F](#) [MF1/4CLT52R1022F](#)
[MF1/4DL2213F](#) [MF1/4DCT52R3013F](#) [MF1/2DLT52R2492F](#) [MF1/2DL2212F](#) [MF1/2CL2212F](#) [MF1/2DL2803F](#)
[MF1/4DL5603F](#) [MF1/2CL2803F](#) [MF1/2CLT52R4532F](#) [MF1/4CL2213F](#) [MF1/2CL2213F](#) [MF1DLT521R27R4F](#)
[MF1/2DL2213F](#) [MF1/4CLT52R10R0F](#) [MF1/4CLT52R1023F](#) [MF1/4DL2212F](#) [MF1/4DL2R21F](#) [MF1/4DL2211F](#)
[MF1/2DLT52R2490F](#) [MF1/4CL2802F](#) [MF1/4CL2212F](#) [MF1/4DL2802F](#) [MF1/2CLT52R2001F](#) [MF1/4DLT26A3652F](#)
[MF1/4CL2803F](#) [MF1/2DL2802F](#) [MF1/2DL2211F](#) [MF1/2CL2802F](#) [MF1/2CL2211F](#) [MF1/4CL2211F](#) [MF1/4DL2803F](#)
[MF1/2CLT52R1471F](#) [MF1/4DLT52R3603F](#) [MF1/4DLT52R1R82F](#) [MF1/4CL51R1F](#) [MF1/4DL51R1F](#)
[MF1/4DCT52R1243F](#) [MF1/2DLT52R2371F](#) [MF1/2CLT52R68R1F](#) [MF1/2DLT52R2370F](#) [MF1/4DLT52R2874F](#)
[MF1/2CLT52R1433F](#)