



SitemapMasthead

english

Search

HOMEPRODUCTSCATALOGUECOMPANYLATEST NEWSERVICECONTACT0 ARTICLES

Heatsinks f.cool

Profile heatsinks and fluid coolers

- Standard extruded heatsinks
- Extruded heatsinks for lock-in retaining spring
- Extruded heatsinks for PCB mounting
- Extruded heatsinks for DC/DC converter
- Retaining springs for transistors
- U-Extruded heatsinks
- Die-cast heatsinks
- Fin coolers
- Fluid coolers
- Aluminium flat-, quadrangular-, angled-, U- & T-profiles

Heatsinks and active heatsinks for processors

Board Level heatsinks

Cooling aggregates

Accessories for electronic components

Cases f.case

Connectors f.con

You are here: Products » Heatsinks f.cool » Profile heatsinks and fluid coolers » Standard extruded heatsinks » SK 42 ... » SK 42

Standard extruded heatsinks

SK 42 ...

SK 42 1000 AL

200 x 25 mm

add to request



Features

Technical Drawing

Service

width

height

plate thickness

length

thermal resistance R_{θ}

surface

200 mm

25 mm

4 mm

1000 mm

1.65 - 0.7 K/W

raw degreased aluminium

Fischer Elektronik GmbH & Co. KG

Nottebohmstraße 28, D - 58511 Lüdenscheid

☎: +49 (0) 23 51 / 4 35 - 0, info@fischer elektronik.de



SitemapMasthead

http://www.fischer elektronik.de/fisch_electro_en_GB/heatsinks/VA/1/Standard%20extruded%20heatsinks/VA/SK421000AL/index.xhtml

1 / 1