



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > 13MM MV OUTPUT PRESSURE SENSOR



Pressure: [30 psi]

Pressure Sensor Type: mV Output Pressure Sensors

Pressure Type: Gauge

Output Signal Type: 100mV

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

All 13MM MV OUTPUT PRESSURE SENSOR (18)

Features

Product Type Features

Pressure Sensor Type	mV Output Pressure Sensors
Pressure Type	Gauge
Sensor Package	Threaded Process Fittings, Weldable

Configuration Features

Electrical Connection	Ribbon Cable
-----------------------	--------------

Electrical Characteristics

Supply Current	1.5 mA
----------------	--------

Dimensions

Product Diameter	15.85 mm[.624 in]
Product Height	9.3 mm[.366 in]

Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Proof Pressure Range	3X
	30 psi
Output Signal Type	100mV



Other

Non-Linearity ±	.1 %
Port Fitting	1/4-18 NPT (7/8 Hex)

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6-trimethylphenyl)- (1% in Component part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # CAT-MIPS0012
13MM MV OUTPUT PRESSURE
SENSOR



TE Part # CAT-MIPS0015
Pressure Sensor, MV Output, 13 mm

Also in the Series

MEAS 85 Series



Media Isolated Pressure Sensors(42)

Customers Also Bought



TE Part #85-300G-4R
300 PSIG 1/4 -18 NPT RIBBON PRESS
SENSOR



TE Part #4515-DS5A005GP
PRESS XDCR,ANALOG,INH20 RANGE



TE Part #FX1901-0001-0010-L
COIN LOADCELL SENSOR



TE Part #85-015V-4C
VACGAGE,1/4NPT,5/8HEX,CBL/CON



TE Part #85-030A-4R
NISO,ABS,1/4 NPT,RIBBON CBL



TE Part #86-030G-CT
NISO,LP,GAGE,CBL/CONNECT/TUB

Documents

- CAD Files
- 3D PDF
- 3D
- Customer View Model
- ENG_CVM_CVM_85-030G-4R_G1.2d_dxf.zip
- English



Customer View Model

[ENG_CVM_CVM_85-030G-4R_G1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_85-030G-4R_G1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[85C](#)

English