

## Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C


## Typical Applications

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

## Mechanical Data

- **Package:** DO-214AA (SMB)  
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

### DO-214AA (SMB)



## ■Maximum Ratings (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                                                                                     | SYMBOL           | UNIT             | GS5AB      | GS5BB | GS5DB | GS5GB | GS5JB | GS5KB | GS5MB |
|-----------------------------------------------------------------------------------------------|------------------|------------------|------------|-------|-------|-------|-------|-------|-------|
| Maximum Repetitive peak reverse voltage                                                       | V <sub>RRM</sub> | V                | 50         | 100   | 200   | 400   | 600   | 800   | 1000  |
| Maximum RMS Voltage                                                                           | V <sub>RMS</sub> | V                | 35         | 70    | 140   | 280   | 420   | 560   | 700   |
| Maximum DC Blocking Voltage                                                                   | V <sub>DC</sub>  | V                | 50         | 100   | 200   | 400   | 600   | 800   | 1000  |
| Average rectified output current<br>@60Hz sine wave, resistance load, TL (Fig.1)              | I <sub>O</sub>   | A                | 5.0        |       |       |       |       |       |       |
| Forward Surge Current (Non-repetitive)<br>@60Hz Half-sine wave, 1 cycle, T <sub>j</sub> =25°C | I <sub>FSM</sub> | A                | 150        |       |       |       |       |       |       |
| Forward Surge Current (Non-repetitive)<br>@1ms, square wave, 1 cycle, T <sub>j</sub> =25°C    |                  |                  | 300        |       |       |       |       |       |       |
| Current squared time<br>@1ms≤t≤8.3ms T <sub>j</sub> =25°C                                     | I <sup>2</sup> t | A <sup>2</sup> s | 94         |       |       |       |       |       |       |
| Storage temperature                                                                           | T <sub>stg</sub> | °C               | -55 ~ +150 |       |       |       |       |       |       |
| Junction temperature                                                                          | T <sub>j</sub>   | °C               | -55 ~ +150 |       |       |       |       |       |       |

## ■Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                                               | SYMBOL         | UNIT | TEST CONDITIONS                                           | GS5AB | GS5BB | GS5DB | GS5GB | GS5JB | GS5KB | GS5MB |
|---------------------------------------------------------|----------------|------|-----------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|
| Maximum instantaneous forward voltage                   | V <sub>F</sub> | V    | I <sub>FM</sub> =5.0A                                     | 1.1   |       |       |       |       |       |       |
| Maximum DC reverse current at rated DC blocking voltage | I <sub>R</sub> | μA   | T <sub>j</sub> =25°C                                      | 5     |       |       |       |       |       |       |
|                                                         |                |      | T <sub>j</sub> =125°C                                     | 100   |       |       |       |       |       |       |
| Typical junction capacitance                            | C <sub>j</sub> | pF   | Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | 34    |       |       |       |       |       |       |

## ■ Thermal Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                  | SYMBOL            | UNIT | GS5AB             | GS5BB | GS5DB | GS5GB | GS5JB | GS5KB | GS5MB |
|----------------------------|-------------------|------|-------------------|-------|-------|-------|-------|-------|-------|
| Typical Thermal resistance | R <sub>θJ-A</sub> | °C/W | 80 <sup>(1)</sup> |       |       |       |       |       |       |
|                            | R <sub>θJ-L</sub> |      | 35 <sup>(1)</sup> |       |       |       |       |       |       |
|                            | R <sub>θJ-C</sub> |      | 30 <sup>(1)</sup> |       |       |       |       |       |       |

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x 8.0 mm) copper pad areas

## ■ Characteristics (Typical)

FIG1: I<sub>o</sub>-T<sub>L</sub> Curve




FIG2: Surge Forward Current Capability




FIG3: Typical Forward Voltage




FIG4: Typical Reverse Characteristics

