



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **8**

Centerline (Pitch): **4.14 mm [.162 in]**

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Header Type                       | Fully Shrouded        |
| Rectangular Power Connector Type  | Header                |
| Connector & Housing Type          | Plug                  |
| Connector System                  | Wire-to-Board         |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

|                            |             |
|----------------------------|-------------|
| Number of Positions        | 8           |
| PCB Mount Orientation      | Right Angle |
| Number of Power Positions  | 8           |
| Number of Signal Positions | 0           |
| Number of Rows             | 2           |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 600 VDC |
|-------------------|---------|



Contact Features

|                                                         |                  |
|---------------------------------------------------------|------------------|
| Multiple Contact Types                                  | Without          |
| PCB Contact Termination Area Plating Material Thickness | 3.81 μm[150 μin] |
| Contact Mating Area Plating Material                    | Gold             |
| Contact Current Rating (Max)                            | 9.5 A            |
| Contact Retention Within Housing                        | Without          |
| Contact Type                                            | Pin              |
| PCB Contact Termination Area Plating Material           | Tin-Lead         |
| Contact Mating Area Plating Material Thickness          | .76 μm[30 μin]   |

Termination Features

|                                |                       |
|--------------------------------|-----------------------|
| Termination Post & Tail Length | 3.69 mm[.145 in]      |
| Termination Method to PCB      | Through Hole - Solder |

Mechanical Attachment

|                          |                 |
|--------------------------|-----------------|
| Strain Relief            | Without         |
| Mating Alignment Type    | Chamfered Edges |
| Mating Retention         | With            |
| Mating Alignment         | With            |
| PCB Mount Alignment      | Without         |
| Panel Mount Feature      | Without         |
| PCB Mount Retention      | With            |
| PCB Mount Retention Type | Boardlock       |
| Mating Retention Type    | Locking Tab     |
| Connector Mounting Type  | Board Mount     |

Housing Features

|                    |                  |
|--------------------|------------------|
| Centerline (Pitch) | 4.14 mm[.162 in] |
| Housing Color      | White            |
| Housing Material   | Nylon            |

Dimensions

|                             |                 |
|-----------------------------|-----------------|
| Connector Height            | 11.86 mm        |
| PCB Thickness (Recommended) | .06 mm[1.57 in] |
| Product Width               | 12.7 mm         |
| Product Length              | 18.14 mm        |
|                             |                 |



|                    |                  |
|--------------------|------------------|
| Row-to-Row Spacing | 4.14 mm[.163 in] |
|--------------------|------------------|

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |       |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

Industry Standards

|                                             |                               |
|---------------------------------------------|-------------------------------|
| CSA Rating                                  | Certified, LR 7189            |
| UL Rating                                   | Recognized                    |
| Compatible With Agency/Standards Products   | CSA, UL                       |
| Compatible With Approved Standards Products | UL E28476                     |
| UL Flammability Rating                      | UL 94V-0                      |
| Glow Wire Rating                            | Standard Part - Not Glow Wire |

Packaging Features

|                    |     |
|--------------------|-----|
| Packaging Quantity | 200 |
| Packaging Method   | Bag |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

|                                                                                                                                        |                                                                                                                                                 |                                                                                                                                              |                                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 794821-1<br/>08P MINI UMNL PLUG HSG</p> |  <p>TE Part # 794192-1<br/>08P MINI UMNL2 PLUG HSG UL94V0</p> |  <p>TE Part # 794772-8<br/>08P MINI UMNL SEAL,DIE CUT</p> |  <p>TE Part # 770579-1<br/>08P MINI UMNL PLUG HSG</p> |
|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|

Also in the Series | Mini-Universal MATE-N-LOK

|                                                                                                                           |                                                                                                                                 |                                                                                                                                |                                                                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
|  <p>Connector Caps &amp; Covers(2)</p> |  <p>Connector Contacts(89)</p>              |  <p>Connector Hardware(4)</p>             |  <p>Connector Seals &amp; Cavity Plugs(17)</p> |
|  <p>Connector Strain Relief(2)</p>     |  <p>Insertion &amp; Extraction Tools(1)</p> |  <p>Rectangular Power Connectors(197)</p> |                                                                                                                                     |

Customers Also Bought

|                                                                                                                                     |                                                                                                                                                   |                                                                                                                                                   |                                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part #1-6609035-4<br/>30ESK6=F7517 S0</p> |  <p>TE Part #1871058-4<br/>PCI EXPRESS CONN. EON TYPE, 16</p> |  <p>TE Part #5-146277-6<br/>06 MODII HDR SRST B/A .100CL</p> |  <p>TE Part #5569262-1<br/>STK MJ ASSY,8POS,2X4,SHLD,CAT5</p> |
|-------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|



TE Part #5555154-2  
[MJ,R/A,LP,F6P/4C,SHLD,PNL,TRAY](#)

TE Part #1055689-1  
[2367 5002 54,VERT PLUG](#)

TE Part #6-104935-3  
[14 MTE HDR SRRA LTCH.100CL LF](#)

TE Part #6-535541-8  
[20 MODIV VRT SR CE 100/115](#)

TE Part #ZPF000000000008886  
[983-6SE 16-24 PN](#)

TE Part #Y79003-14-19PNV004  
[HERM RECP](#)

Documents

Product Drawings

[08P MINI UMNL R/A HDR ASSY LF](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_1-770970-1\\_E.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-770970-1\\_E.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-770970-1\\_E.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT\\_SHELL\\_PIN\\_AND\\_SOCKET\\_CONNECTORS\\_CATALOG](#)

English

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)



English

Agency Approvals

UL

English