





Heyco® Straight-Thru Strain Relief Bushings

For Flat Cables, With Flex-Protecting Internal Radii
Extra Body Length SR-4

- Protects the lifeline of your electric/electronic products by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cable at panel entry points.
- Sizes for narrow .040" (1,0mm) panel available: SR 3A-4, SR 4A-6. See charts for details.
- Standardize panel design! Fill unused SR mounting holes with Heyco Double "D" Plugs, page 2-21.
- See page 2-24, 2-25, and 2-26 for assembly tools and SR hole punches.
- See page 2-15 for Quick Specs.



*To install strain reliefs for .040" (1,0mm) maximum panel thickness, use **Part #0021** (No. R-291) Hand Pliers.

WILL FIT THESE CABLES				PANEL DIMENSIONS				PART NO.		DESCRIPTION	C BODY LENGTH	
UL Type Designation	AWG/Conductors	Approximate Size		A Mounting Hole Dia.	B To Prevent Rotation	Maximum Panel Thickness		Black	White		in.	mm.
		in.	mm.	in.	mm.	in.	mm.					
SPT-1	18/3	.12x.30	3,0x7,6									
SPT-2 & HPN	18/2	.15x.28	3,8x7,1	.500	12,7	.465	11,8	.040*	1,0	1181 1182	SR 4A-6	.546 13,9
Same as SR-4A-6 above except								.062	1,6	1187 1188	SR 4N-6	.546 13,9
Same as SR-4A-6 above except								.100	2,5	1190 1191	SR 4K-6	.546 13,9

Standard Colors: Black or White. Consult Heyco for other colors. Consult factory for color matching, prices, and minimum order quantities.

For Flat Cables, With Flex-Protecting Internal Radii

WILL FIT THESE CABLES				PANEL DIMENSIONS				PART NO.		DESCRIPTION	C BODY LENGTH	
UL Type Designation	AWG/Conductors	Approximate Size		A Mounting Hole Dia.	B To Prevent Rotation	Maximum Panel Thickness		Black	White		in.	mm.
		in.	mm.	in.	mm.	in.	mm.					
CLOCK	20/2	.09x.18	2,3x4,6	.375	9,5	.345	8,8	.062	1,6	1017 1018	SR 2P-4	.406 10,3
SPT-1	18/2	.11x.21	2,8x5,3									
Same as SR 2P-4 above except								.125	3,2	1034 1035	SR 2L-1	.406 10,3
SPT-1	18/2	.12x.22	3,0x5,6	.437	11,1	.390	9,9	.040*	1,0	1074 1075	SR 3A-4	.406 10,3
Same as SR 3A-4 above except								.062	1,6	1077 1078	SR 3P-4	.406 10,3
								.100	2,5	1104 1105	SR 3W-1	.406 10,3
								.156	4,0	1094 1095	SR 3L-1	.406 10,3
SPT-1	18/2	.12x.22	3,0x5,6	.500	12,7	.445	11,3	.100	2,5	1130 1131	SR 4P-4	.440 11,2
SPT-1	18/3	.12x.30	3,0x7,6	.500	12,7	.465	11,8	.062	1,6	1120 1121	SR 4N-4	.406 10,3
HPN	18/2	.15x.28	3,8x7,1									
Same as SR 4N-4 above except								.100	2,5	1117 1118	SR 4K-4	.406 10,3
								.156	4,0	1127 1128	SR 4L-4	.406 10,3
SPT-1	18/3	.12x.30	3,0x7,6	.500	12,7							
SPT-2 & HPN	18/2	.15x.28	3,8x7,1	.500	12,7							
HPN	18/3	.15x.34	3,8x8,6	.500-.515	12,7-13,1	.460	11,7	.095	2,4	1114 1115	SR 4K-1	.500 12,7
SPT-2 & HPN	16/2	.16x.30	4,1x7,6									
Same as SR 4K-1 above except								.187	4,7	1124 1125	SR 4L-1	.500 12,7
SPT-3	18/2	.19x.35	4,8x8,9	.562	14,3	.530	13,5	.062	1,6	1170 1171	SR 5KN-4	.609 15,5
SPT-2	18/3	.15x.40	3,8x10,2									
	16/3	.16x.41	4,1x10,4									
Same as SR 5KN-4 above except								.125	3,2	1167 1168	SR 5K-4	.609 15,5
SPT-2	18/3	.15x.40	3,8x10,2	.625	15,9	.550	14,0	.062	1,6	1160 1161	SR 6N4-4	.578 14,7
	16/3	.16x.41	4,1x10,4									
Same as SR 6N4-4 above except								.125	2,5	1163 1164	SR 6P4-4	.578 14,7

Standard Colors: Black or White. Consult Heyco for other colors. Consult factory for color matching, prices, and minimum order quantities.