


Actuator

704.510.008

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/704.510.008>

Your product:



704.510.008 Actuator

FRONT

Front bezel colour:	Silver
Front bezel material:	Plastic
Front dimension:	35 mm x 35 mm

MOUNTING

Mounting cut-out:	30 mm x 30 mm
Design:	flush

OPERATING-/INDICATION PART

Lever colour:	Black
Lever material:	plastic
Lever shape:	short

ELECTRICAL CHARACTERISTICS

Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
------------	---

MECHANICAL CHARACTERISTIC


Mechanical lifetime:	≤2.5 Mio. cycles of operation
Switching action:	Rest - Maintained
Weight:	0.056 kg
Switching angle:	90° right / -45° ... +45°
Switching positions:	2 positions

AMBIENT CONDITION


IP Protection:	IP65 front side
Storage temperature:	– 40 °C ... + 85 °C
Operating temperature:	– 40 °C ... + 55 °C

OTHER

Hints:	Max. 3 switching elements can be clipped on
Short Description:	Actuator, 30 mm x 30 mm, 35 mm x 35 mm, non illuminative, Black, short, Silver, Plastic, Rest - Maintained
max. number of switching elements:	3
Switching positions:	




Dimension drawings:



A = Screw terminal

Mounting cut-outs:



A = Screw terminal
 B = Push-in terminal (PIT)
 C = Plug-in terminal 6.3 mm x 0.8 mm
 D = Double plug-in terminal 6.3 mm x 0.8 mm

Wiring diagrams:

