

## Honeywell Sensing and Control

Search

**2TL1-56N**

( Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TL )


## narrow your search

## Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1701)
- Sensors (6224)
- Switches (9749)
- Wireless (39)

## Technology

- Control and Instrumentation (1052)
- Electromechanical (9301)
- Magnetic (541)
- Optical/Infrared (1042)
- Thick Film (1764)
- More...



TL Series Toggle Switch, 2 pole, 3 position, Screw terminal, Locking Lever, Military Part Number MS27408-2N

Actual product appearance may vary.

Sales &amp; Service

Distributor Inventory

## contacts

Customer Service  
Technical Support  
Global Sales & Service  
View Site Demo  
Site Comments?

## meet dr. larry

**VIDEO** - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



## my links

Login to iCOM  
Login to Rep/AD Portal  
Login to Digital University

## new products

## New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site  
WGLA and WPMM  
XYR6000™

find out more

## white papers

Wireless Switches Offer Unlimited Benefit  
Basic Switches Are Not Created Equal  
Applying Precision Switches  
Sensors for Medical Devices  
New Ways to Measure Torque  
Choosing Safety Switches  
Specifying Hour Meters


## Need help?

[Click here to contact us](#)

Overview Specs Documentation Application Notes

## Product Specifications

Circuitry/Operating action



MICRO SWITCH™ Toggle Switch



Locked out of extreme position (Opposite keyway)

Product Type  
Lever Lock

Ampere/Voltage Range (Resistive Load)

Circuitry

Action

Mounting

Termination

MIL Spec. Number

Lever Type

UL/CSA

Comment

Availability

UNSPSC Code

UNSPSC Commodity

Series Name

0.5 A to 10 A at 0.5 Vac to 277 Vac, 0.5 A at 250 Vdc, 0.75 A at 115 Vdc, 0.5 A to 18 A at 0.5 Vdc to 28 Vdc

DPDT

3 position

Bushing 15/32 in

Screw

MS27408-2N

Locking

L192: 10 A-125, 250, 277 Vac; 1/4 Hp-125 Vac; 1/2 Hp-250, 277 Vac; 3 A-125 Vac "L"

Silver cadmium oxide contacts

Global

30211908

30211908 Toggle switches

TL

## News Center

HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING

HONEYWELL RELEASES UNLIMITED POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES

HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS

**MICRO SWITCH Anniversary site**