

Direct Links

Cross Reference

RoHS/LF P/N search

Document & Drawing search

Application tooling

Services

Contact us

Distributor list

Pricing request

Order samples

Literature

Brochures & catalogs

Product documentation

Technical library

HM2P70PKE121GF

[Assistant](#) [Add to Favorites](#)



HM2P70PKE121GF - **Millipacs™**

2 mm Hardmetric Series 5 Row
Straight Press-Fit Header Type B22
with 110 Signal pins

ACTIVE

[Customer
Drawing](#)

Electronics division

☒ [Email Datasheet](#) ☐ [Print Datasheet](#)

FCI Brings You More

- ☒ [Contact our sales/technical support...](#)
- ☒ [Sample request](#)
- ☐ [Price request](#)
- ☐ [Check distributor stock](#)

Alternate Products



[HM2P70PKE121GFLE...](#)
2 mm Hardmetric Series 5 Row Straight
Press-Fit Header Type B22 with 110 Signal
pins and RoHS compatible

Download document

Technical Resources

- ☐ [> 3D IGES](#)
- ☐ [> Product Specification...](#)
- ☐ [> 3D PROE](#)

Literature

- ☐ [> Connectors for Medical...
Devices Brochure](#)
- ☐ [> Connector Overview Brochure...](#)

Application Tooling

- ☐ [> Asia Pacific Application...
Tooling..](#)
- ☐ [> Americas Application Tooling....](#)
- ☐ [> Europe Application Tooling....](#)

Specifications

General Dimensional Electrical Mechanical Mounting Physical Approvals /
Certifications

General	
Gender	Header
Number of contacts	110
Number of rows	5
Orientation	Straight
Product Type	Header
Series	Module Type B (22 Pos)
Shielded	Yes
Number of levels (Contact)	Refer to Customer Drawing
Dimensional	
Length (Tail)	Rear Mating Tail Level 1 (13 mm)
Electrical	
Current rating	1.5A @ 20°C, 1A @ 70°C
Resistance (Contact)	20 milli ohms max
Resistance (Insulation)	10000 mega ohms min
Voltage rating	750V rms
Mechanical	
Withdrawal Force	0.15N min. Per contact pai
Hertz stress	200 Kpsi min.
Mating force (Signal)	0.75N max. Per contact pai
Normal force (Signal)	0.75N min. (EOL
Mounting	
Mounting style (Board)	Press-Fit
Physical	
Finish (Contact)	Level 2
Material (Contact)	Phospher Bronze
Material (Housing)	Thermoplastic (UL94 V-0)
Temperature (Operating)	-55°C to +125°C
Approvals / Certifications	
Approvals / Certifications	UL and CSA Certifiec