




SPECIFICATION

MATERIAL:

INSULATOR: HIGH TEMPERATURE THERMOPLASTIC,
UL 94V-0. COLOR: BLACK LCP

CONTACT: COPPER ALLOY

PLATING:

CONTACT: PLATED 30U" NI OVERALL
PLATED AU SELECTIVE CONTACT AREA

SHELL: PLATED 30U" NI OVERALL, PAD G/F AU

ELECTRICAL:

CURRENT RATING: 0.5AMPS

VOLTAGE RATING: 5V AC/DC

AMBIENT TEMPERATURE RANGE: -40°C~+85°C

STORAGE TEMPERATURE RANGE: -40°C~+85°C

AMBIENT HUMIDITY RANGE: 95% R.H. MAX.

CONTACT RESISTANCE: 100MΩ MAX.

INSULATION RESISTANCE: 1000MΩ MIN./500VDC

MATING CYCLES: 5,000 INSERTIONS

REFLOW PEAK TEMP: 260°C

MINI SIM CARD	
Pin No.	NAME
C1	VCC OF SIM
C2	RST OF SIM
C3	CLK OF SIM
C5	GND OF SIM
C6	VPP OF SIM
C7	I/O OF SIM
C4/C8	N/A
SW1	DETECTION SWITCH1
SW2	DETECTION SWITCH2

▨ PAD AREA

■ KEEP OUT AREA






RECOMMENDED PCB LAYOUT

GENERAL TOLERANCE ±0.05

Circuit Diagram for Detect Switch

WITHOUT CARD	OPEN	OPEN SW1 SW2
INSERTING CARD	CLOSE	CLOSE SW1 SW2

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES		TITLE: MINI SIM CARD PUSH PUSH 6P+2P SMT无柱	
DECIMALS:	ANGLES: ±1°	PAR	SIM-117-ARP8
X.X: ±0.25		DWN	
X.XX: ±0.10		CHKD	
X.XXX: ±0.05		APVD	
CUSTOMER COPY		SCALE: 1:1	UNIT: MM
		SIZE: A4	SHEET: 1F1
			REV: A



一:

- 1.将成品一一放入包装盘内,依同一方向放入
- 2.包装时,如图所示.
- 3.一个包装然放置700个成品

二:

- 1.一只纸箱可放置3个或5个包装盘
- 2.一只纸箱可放2100PCS或4200PCS的成品
- 3.将成品放入包装盘内包装完后再装箱

Note: PULL OUT DIRECTION

- 1.10 sprocket hole pitch cumulative tolerance ± 0.2
- 2.Carrier camber is within 1 mm in 250mm.
- 3.Material:Black Conductive Polystyrene Alloy 100
- 4.All dimensions meet EIA-481-B requirements.
- 5.Thickness: 0.3 ± 0.05 mm.
- 6.Component load per 13" reel: 700 pcs.
7. A box of 3 volumes, 2100PCS
- 8.纸箱规格一: 345*345*165, 纸箱重为300g, (一箱装2100PCS)
- 9.纸箱规格二: 345*345*315, 纸箱重为500g, (一箱装4200PCS)
- 10.重量: 每盘700PCS重1470g, 每Pcs重1.3g/Pcs

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd		
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE:MINI SIM CARD PUSH PUSH 6P+2P SMT无柱 包装图	
			PAR	SIM-117-ARP8
			DWN	
DECIMALS:	ANGLES:±1°		CHKD	
X.X:±0.25			APVD	
X.XX:±0.10		SCALE1:1	UNIT:MM	
X.XXX:±0.05		CUSTOMER COPY	SIZE:A4	SHEET:1F1
				REV:A