Data Sheet



Coaxial Panel Connector 13_BMA-50-0-2/199_N

Description

Straight panel receptacle plug, flange mount

Interface standards IEC 60169-33_MIL-STD-348A/321



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 18 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 1000 Weight 0.0025 kg

Environmental Data

Operating temperature $$-65\ ^{\circ}\text{C}$$ to 125 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	

Related Documents

Catalogue drawing DCA-00011086

Ordering Information

Single package 13_BMA-50-0-2/199_NE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 13_BMA-50-0-2/199_NE