

SCREW-ON MALE RECEPTACLE

HERMETIC-WITH CYLINDRICAL CONTACT

R128.639.020


Series: BMA







All dimensions are in mm.



Issue: 1411 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



SCREW-ON MALE RECEPTACLE

R128.639.020

HERMETIC-WITH CYLINDRICAL CONTACT

Series: **BMA**

PACKAGING

Standard	Unit	Other
1	-	Contact us

SPECIFICATION

ELECTRICAL CHARACTERISTICS

Impedance **50** Ω Frequency **0-22** GHz

VSWR

1.04 + **0.0090** x F(GHz) Maxi Insertion loss **0.03** $\sqrt{F(GHz)}$ dB Maxi

NA - F(GHz)) dB mini RF leakage

- (Voltage rating 500 Veff Maxi

Dielectric withstanding voltage 1500 Veff mini Insulation resistance **5000** MΩ mini

ENVIRONMENTAL

Operating temperature -65/+125 ° C

Hermetic seal **10-8** Atm.cm3/s

Panel leakage NA

OTHERS CHARACTERISTICS

Assembly instruction NA

Others:

MECHANICAL CHARACTERISTICS

Center contact retention

Axial force – Mating end 27 N mini Axial force – Opposite end 27 N mini Torque NA N.cm mini

Recommended torque

Mating NA N.cm Panel nut 280 N.cm

Mating life 1000 Cycles mini

Weight **1,2320** g

Issue: 1411 B

In the effort to improve our products, we reserve the right to make changes judged to be




SCREW-ON MALE RECEPTACLE


R128.639.020

HERMETIC-WITH CYLINDRICAL CONTACT

Series: BMA



MOUNTING HOLE DETAIL



Issue: 1411 B In the effort to improve our products, we reserve the right to make changes judged to be necessary.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Radiall:

R128639020