


# MALE PCB PINS

## SOLDER TERMINALS SLOTTED

### 2104

2104-X-01-XX-00-00-07-0

Swage mount in .036 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 2104-1            | .031            | .055     |
| 2104-2            | .062            | .086     |
| 2104-3            | .094            | .117     |
| 2104-4            | .125            | .148     |

### 2112

2112-X-01-XX-00-00-07-0

Swage mount in .043 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 2112-5            | .016            | .037     |
| 2112-1            | .031            | .053     |
| 2112-2            | .062            | .084     |
| 2112-3            | .094            | .115     |
| 2112-4            | .125            | .147     |

### 2105

2105-X-01-XX-00-00-07-0

Swage mount in .052 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 2105-1            | .031            | .055     |
| 2105-2            | .062            | .086     |
| 2105-3            | .094            | .117     |
| 2105-4            | .125            | .149     |

### 2103

2103-X-01-XX-00-00-07-0

Swage mount in .052 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 2103-1            | .031            | .055     |
| 2103-2            | .062            | .086     |
| 2103-3            | .094            | .117     |
| 2103-4            | .125            | .149     |

### 2106

2106-X-01-XX-00-00-07-0


Swage mount in .052 hole



### 2107

2107-X-01-XX-00-00-07-0

Swage mount in .052 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 210X-1            | .031            | .051     |
| 210X-2            | .062            | .082     |
| 210X-3            | .094            | .113     |
| 210X-4            | .125            | .145     |

### 6620

6620-0-35-XX-00-00-03-0

Solder mount in .064 mounting hole



#### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
( Swage pins are annealed )

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$

RoHS-2  
2011/65/EU

ORDER CODE: XXXX - X - 01 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- ◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- ◆ 44 300  $\mu$ " SILVER OVER COPPER (RoHS)
- 50 300  $\mu$ " ELECTRO-SOLDER  
(60/40 SnPb)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com